

1 LOCATION OF WATER WELL: 105 Fraction SW 1/4 NW 1/4 NW 1/4 Section Number 21 Township Number T 11 S Range Number R 25 EW  
 County: Wyandotte

Distance and direction from nearest town or city street address of well if located within city?

1806 Kansas Avenue, Kansas City, Kansas 66105

MW-6

2 WATER WELL OWNER: Colgate Palmolive Company  
 RR#, St. Address, Box #: 1806 Kansas Avenue  
 City, State, ZIP Code: Kansas City, Kansas 66105

Board of Agriculture, Division of Water Resources

Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 50.0 ft. ELEVATION: 760.5

Depth(s) Groundwater Encountered 1. 40.0 ft. 2. 38.6 ft. 3. ft.

WELL'S STATIC WATER LEVEL 38.6 ft. below land surface measured on mo/day/yr 1/6/95

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 8.25 in. to 50 ft. and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:

5 Wrought iron

8 Concrete tile

CASING JOINTS: Glued Clamped

1 Steel

3 RMP (SR)

6 Asbestos-Cement

9 Other (specify below)

Welded

2 PVC

4 ABS

7 Fiberglass

Threaded

Blank casing diameter 2 in. to 35 ft. Dia. in. to ft. Dia. in. to ft.

Casing height above land surface -4 in. weight 40 lbs./ft. Wall thickness or gauge No.

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel

3 Stainless steel

5 Fiberglass

7 PVC

10 Asbestos-cement

2 Brass

4 Galvanized steel

6 Concrete tile

8 RMP (SR)

11 Other (specify)

9 ABS

12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot

3 Mill slot

5 Gauzed wrapped

8 Saw cut

11 None (open hole)

2 Louvered shutter

4 Key punched

6 Wire wrapped

9 Drilled holes

7 Torch cut

10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 35.0 ft. to 50.0 ft. From ft. to ft.

From ft. to ft. From ft. to ft.

GRAVEL PACK INTERVALS: From 30.0 ft. to 50.0 ft. From ft. to ft.

From ft. to ft. From ft. to ft.

6 GROUT MATERIAL:

1 Neat cement

2 Cement grout

3 Bentonite

4 Other

Concrete

Grout Intervals: From 2.0 ft. to 30.0 ft. From ft. to ft. From 0 ft. to 2 ft.

What is the nearest source of possible contamination:

1 Septic tank

4 Lateral lines

7 Pit privy

10 Livestock pens

14 Abandoned water well

2 Sewer lines

5 Cess pool

8 Sewage lagoon

11 Fuel storage

15 Oil well/Gas well

3 Watertight sewer lines

6 Seepage pit

9 Feedyard

12 Fertilizer storage

16 Other (specify below)

13 Insecticide storage

Direction from well?

How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0.0	8.0	Fill fr stone, cinders & brick			
8.0	13.5	Silt trace clay with sand lenses			
13.5	15.5	F-med silty sand			
15.5	17.0	Silt trace clay with sand layers			
17.0	50.0	F-med sand occ. silty seams			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12/15/94 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 1/6/95

under the business name of Terracon Consultants, Inc. by (signature) Ronald M. White