

1 LOCATION OF WATER WELL: County: Wyandotte		Fraction SE 1/4 NW 1/4 NW 1/4	Section Number 21	Township Number T 11 S	Range Number R 25 EW
Distance and direction from nearest town or city street address of well if located within city? 1806 Kansas Avenue, Kansas City, Kansas 66105 MW 12					
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :		Colgate Palmolive Company 1806 Kansas Avenue Kansas City, Kansas 66105			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 49.5 ft. ELEVATION: 759.5 Depth(s) Groundwater Encountered: 41 ft. 2. 39.1 ft. 3. ft. WELL'S STATIC WATER LEVEL 39.1 ft. below land surface measured on mo/day/yr 2/21/95 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm Well water was ft. after hours pumping gpm Bore Hole Diameter: 6.25 in. to 50 ft., and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only ☒ Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was sub- mitted Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile ☒ PVC 4 ABS 7 Fiberglass Blank casing diameter 2 in. to 34.5 ft., Dia in. to ft. , Dia in. to ft. Casing height above land surface -2 in., weight lbs./ft. Wall thickness or gauge No. sch 40		CASING JOINTS: Glued Clamped Welded Threaded X			
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot ☒ Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)		TYPE OF SCREEN OR PERFORATION MATERIAL: ☒ PVC 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)			
SCREEN-PERFORATED INTERVALS: From 34.5 ft. to 49.5 ft., From ft. to ft. From ft. to ft. , From ft. to ft. GRAVEL PACK INTERVALS: From 32.5 ft. to 49.5 ft., From ft. to ft. From ft. to ft. , From ft. to ft.		6 GROUT MATERIAL: 1 Neat cement 2 Cement grout ☒ Bentonite ☒ Other Concrete Grout Intervals: From 2 ft. to 32.5 ft., From ft. to ft. , From ft. to 2 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? How many feet?			
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS 0 5.5 Fill, sand, clay, or stone brick 0 5.5 5.5 10.5 Cinders 10.5 12.5 Silty clay with silty layers Gr Brown 12.5 14 Fine to medium sand with silty clay 14 50 Seams Brown 14 50 Light Fat clay Brown 14 50 Fine to coarse sand Brown					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2/17/95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 3/6/95 under the business name of Terracon Consultants, Inc. by (signature) Ronald S. Little					