


1 LOCATION OF WATER WELL: County: Geary Fraction: NE 1/4 NW 1/4 SE 1/4 Section Number: 2 Township Number: T 11 S Range Number: R 4 E
 Distance and direction from nearest town or city street address of well if located within city? From water park go 1 1/2 miles west on 82 Hwy to Blacktop Road & go south 10 miles to Reynolds Rd. & 1/2 mile east

2 WATER WELL OWNER: Lance Boyer
 RR#, St. Address, Box #: 1697 3325 Av. Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Abilene KS 67410 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 120 ft. ELEVATION:
 Depth(s) Groundwater Encountered: 1 ft. 2 ft. 3 ft.
 WELL'S STATIC WATER LEVEL: 60 7/8 ft. below land surface measured on mo/day/yr
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield: 207 gpm Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS:
 Domestic Feedlot 5 Public water supply 8 Air conditioning 11 Injection well
 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 7 Domestic (lawn & garden) 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was submitted
 Water Well Disinfected: Yes No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter: 5 in. to 100 ft. Dia. in. to ft. Dia. in. to ft.
 Casing height above land surface: 21 in., weight: Sch 40 lbs./ft. Wall thickness or gauge No.
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 10 Asbestos-Cement
 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RMP (SR) 11 Other (Specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 25/1900's
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) ft.
 SCREEN-PERFORATED INTERVALS: From 100 ft. to 120 ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 25 ft. to 120 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 5 ft. to 25 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? NORTH EAST How many feet? 200'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	Top Soil			
1	9	Brown Clay			
9	14	Limestone			
14	36	Yellow Shale			
36	39	Limestone			
39	71	Brown Shale (water)			
71	105	Limestone			
105	108	Greenish Shale			
108	116	Limestone			
116	120	Grey clay shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12/2/2004 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 457 This Water Well Record was completed on (mo/day/yr) 12/16/2004 under the business name of Halkman Well Drilling by (signature) Craig W. Campbell