


1 LOCATION OF WATER WELL: Fraction SW 1/4 SW 1/4 NW 1/4 Section Number 30 Township Number T 11 S Range Number R 4 E/W*
 County: Dickinson

Distance and direction from nearest town or city street address of well if located within city?
5 miles North of Chapman, Ks go 1 mile West & 1/2 mile North on Quail Rd at

2 WATER WELL OWNER: Dale Stein 3250 Quail Rd
 RR#, St. Address, Box # : 3250 Quail Rd Board of Agriculture, Division of Water Resources
 City, State, ZIP Code : Chapman, Kansas 67431 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL 5.8 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1 1.8 ft. 2 ft. 3 ft.
 WELL'S STATIC WATER LEVEL 1.5 ft. below land surface measured on mo/day/yr 7 / 21 / 05
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield 5 gpm: Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well
 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 7 Domestic (lawn & garden) 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No *; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes * No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued * Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter 5 in. to 5.8 ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface 2.4 in., weight 2.00 lbs./ft. Wall thickness or gauge No. 2.50
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 10 Asbestos-Cement
 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RMP (SR) 11 Other (Specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) ft.
 SCREEN-PERFORATED INTERVALS: From 1.8 ft. to 5.8 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 1.5 ft. to 5.8 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout intervals: From 0 ft. to 1.5 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? SOUTH APPROX How many feet? 110

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	DARK TOP SOIL			
2	9	BROWN CLAY			
9	13	LIMESTONE HARD			
13	23	LITE COLOR SHALE			
23	26	LITE COLOR LIMESTONE			
26	32	LITE COLOR SHALE			
32	40	GRAY SHALE & CLAY			
40	42	HARD LIMESTONE			
42	43	TAN CLAY & SHALE			
43	49	GRAY CLAY			
49	50	HARD DARK LIMESTONE			
50	55	GRAY SHALE & CLAY			
55	58	GRAY & MAROON CLAY MIXED			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7 / 21 / 05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 39.7 This Water Well Record was completed on (mo/day/yr) 7 / 25 / 05 under the business name of CENTRAL KANSAS DRILLING by (signature) Harold R. Martin