


1 LOCATION OF WATER WELL: Fraction SW 1/4 SW 1/4 SW 1/4 Section Number 9023 Township Number T 23 S Range Number R 4 W
 County: Grady

Distance and direction from nearest town or city street address of well if located within city? From J.C. 60th MILLS HWY on 244 to DITRICK RD. & GO NORTH 1 MILE & EAST 1/2 MILE ON ST. JOHN'S RD.

2 WATER WELL OWNER: St Johns Holms
 RR#, St. Address, Box #: P.O. Box 263 Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Wakefield, KS 67489 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 158 ft. ELEVATION:
 Depth(s) Groundwater Encountered: 158.5 ft. 2 ft. 3 ft.
 WELL'S STATIC WATER LEVEL: 80 ft. below land surface measured on mo/day/yr
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield: 20 gpm: Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? No; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 Blank casing diameter: 5" in. to 138 ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface: 2' in., weight 5ch. 40 lbs./ft. Wall thickness or guage No.
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 10 Asbestos-Cement
 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RMP (SR) 11 Other (Specify)
 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Guazed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) ft.
 SCREEN-PERFORATED INTERVALS: From 138 ft. to 158 ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 25 ft. to 158 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 3 ft. to 25 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines None Close 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
1	12	Brown clay			
12	15	Limestone			
15	25	Greenish shale			
25	38	Limestone			
38	85	Brown shale			
85	150	Limestone			
150	158	Gray city shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3/6/2006 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 45. This Water Well Record was completed on (mo/day/yr) 3/23/2006 under the business name of Haldeman well Drilling by (signature) Ray L. Carpenter