

USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

1. Location of well:	County GEARY	Fraction NW 1/4 NW 1/4 NW 1/4	Section number 10	Township number T 11 S	Range number R 5 E/W
2. Distance and direction from nearest town or city: Street address of well location if in city: 1/2 W - 43/4 N Junction City			3. Owner of well: HAYES BECK R.R. or street: City, state, zip code: JUNCTION CITY, KS		
4. Locate with "X" in section below: N W E S 1 Mile 1 Mile			Sketch map: well X House DRAINAGE 150'		
5. Type and color of material			From	To	6. Bore hole dia. 8 in. Completion date 7-1-76 Well depth 160 ft.
Top soil			0	4	7. Cable tool <input checked="" type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary
yellow shale			4	9	8. Use: <input checked="" type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other
grey Lime			9	27	9. Casing: Material PVC Height: 5 above or below Threaded <input type="checkbox"/> Welded <input type="checkbox"/> Surface 24 in. RMP PVC 92 Weight 2.58 lbs./ft. Dia. 5 in. to 160 ft. depth Wall Thickness: inches or Dia. 5 in. to 160 ft. depth gage No. 258
yellow shale			27	93	10. Screen: Manufacturer's name PUMPCO Type PVC Dia. 5 Slow gauze 060 Length 20 Set between 90 ft. and 110 ft. ft. and 110 ft. Gravel pack? <input checked="" type="checkbox"/> Size range of material 1/4 X 1/8
yellow Lime (109pm)			93	97	11. Static water level: 90 ft. below land surface Date 7-1-76 mo./day/yr.
yellow shale			97	119	12. Pumping level below land surfaces: ft. after _____ hrs. pumping _____ g.p.m. ft. after _____ hrs. pumping _____ g.p.m. Estimated maximum yield 10 g.p.m.
grey Lime			119	121	13. Water sample submitted: _____ mo./day/yr. Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Date _____
Red shale			121	147	14. Well head completion: CAP Pitless adapter 24 Inches above grade
grey Lime			147	150	15. Well grouted? <input checked="" type="checkbox"/> With: <input checked="" type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input type="checkbox"/> Concrete Depth: From 5 ft. to 15 ft.
Red shale			150	160	16. Nearest source of possible contamination: ft. 150 Direction S Type SEPTIC Well disinfected upon completion? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
(Use a second sheet if needed)					17. Pump: <input checked="" type="checkbox"/> Not installed Manufacturer's name _____ Model number _____ HP _____ Volts _____ Length of drop pipe _____ ft. capacity _____ g.p.m. Type: <input type="checkbox"/> Submersible <input type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other
18. Elevation: Topography: <input checked="" type="checkbox"/> Hill <input type="checkbox"/> Slope <input type="checkbox"/> Upland <input type="checkbox"/> Valley	19. Remarks: OWNER WILL INSTAL SLAB		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Strader Dale Co Inc 182 Business name License No. Address PTI HAITON, KS Signed Dale Robson Date 7-6-76 Authorized representative		