

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: SEMI Riley		NE 1/4 NW 1/4 SE 1/4	12	T 11 S	R 5 EW
Distance and direction from nearest town or city street address of well if located within city? RR 3, Junction City, KS mu-5					
2 WATER WELL OWNER: SPIRIT OF '98					
RR#, St. Address, Box # : PO BOX 1876					
City, State, ZIP Code : Junction, City, KS 66441					
Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 23.7 ft. ELEVATION: 1071.16			
		Depth(s) Groundwater Encountered 1. 17.0 ft. 2. - ft. 3. - ft.			
		WELL'S STATIC WATER LEVEL 18.72 ft. below land surface measured on mo/day/yr 5-6-93			
		Pump test data: Well water was - ft. after - hours pumping - gpm			
		Est. Yield - gpm: Well water was - ft. after - hours pumping - gpm			
		Bore Hole Diameter 8 in. to 25.5 ft. and - in. to - ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes - No X If yes, mo/day/yr sample was sub-			
		mitted			
		Water Well Disinfected? Yes - No X			
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued - Clamped -					
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded -					
Blank casing diameter 2 in. to 13.7 ft., Dia - in. to - ft., Dia - in. to - ft.					
Casing height above land surface - 1.6 in., weight - lbs./ft. Wall thickness or gauge No. 40					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) -					
12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)					
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes					
7 Torch cut 10 Other (specify) -					
SCREEN-PERFORATED INTERVALS: From 23.7 ft. to 13.7 ft. From - ft. to - ft.					
GRAVEL PACK INTERVALS: From 25.5 ft. to 11.5 ft. From - ft. to - ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Concrete 0'-1'					
Grout Intervals: From 11.5 ft. to 1.0 ft. From - ft. to - ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
13 Insecticide storage					
Direction from well? WSW WSW How many feet? 320					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	0.3	ASPHALT			
0.3	4.5	DARK GREY SILTY CLAY			
4.5	5.5	GREY SANDY SILTY CLAY			
5.5	20.0	LT. BROWN-GREY FINE GRAIN SAND			
20.0	25.5	GREY LT. BROWN MED COARSE GRAIN SAND			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-4-93 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 510 This Water Well Record was completed on (mo/day/yr) 7-22-93					
under the business name of MIKON Corporation by (signature) David Kramer					