

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:	County Geary	Fraction SE 1/4 NE 1/4 NW 1/4	Section number 21	Township number T 11 S R 5	Range number 5	E XX																					
2. Distance and direction from nearest town or city: 3 miles NW of Junction City Street address of well location if in city:			3. Owner of well: Municipal Golf Course R.R. or street: Junction City City, state, zip code: Kansas 66441																								
4. Locate with "X" in section below: <div style="display: flex; align-items: center; margin-top: 10px;"> <div style="margin-right: 20px;"> <p>Sketch map:</p> </div> <div> <p>Well A is located 300' West of Test Hole 1-78; completed March 29, 1978</p> </div> </div>			6. Bore hole dia. 48 in. Completion date Well depth 55 ft. 4/26/79																								
5. Type and color of material <table border="1" style="width:100%; border-collapse: collapse; margin-top: 10px;"> <thead> <tr> <th style="width:80%;"></th> <th style="width:10%;">From</th> <th style="width:10%;">To</th> </tr> </thead> <tbody> <tr> <td>Soil</td> <td>0</td> <td>3</td> </tr> <tr> <td>Brown silt</td> <td>3</td> <td>12</td> </tr> <tr> <td>Fine to med. sand</td> <td>12</td> <td>17</td> </tr> <tr> <td>Med. to coarse sand & gravel</td> <td>17</td> <td>48</td> </tr> <tr> <td>Flat rock w/med. sand & gravel</td> <td>48</td> <td>52</td> </tr> <tr> <td>Blue shale</td> <td>52</td> <td></td> </tr> </tbody> </table>				From	To	Soil	0	3	Brown silt	3	12	Fine to med. sand	12	17	Med. to coarse sand & gravel	17	48	Flat rock w/med. sand & gravel	48	52	Blue shale	52		7. <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary			
	From	To																									
Soil	0	3																									
Brown silt	3	12																									
Fine to med. sand	12	17																									
Med. to coarse sand & gravel	17	48																									
Flat rock w/med. sand & gravel	48	52																									
Blue shale	52																										
			8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other																								
			9. Casing: Material steel Height: Above or below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 36 in. RMP <input type="checkbox"/> PVC <input type="checkbox"/> Weight 43.77 lbs./ft. Dia. 12 in. to 32 ft. depth Wall Thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth gage No. .330"																								
			10. Screen: Manufacturer's name Layne & Bowler, Inc. Type S.S. Shutter Dia. 12" Slot/gauze .105" Length 20' Set between 32 ft. and 52 ft. Gravel pack? Yes Size range of material 1/8-1/4																								
			11. Static water level: 13.9 ft. below land surface Date 9/29/78 mo./day/yr.																								
			12. Pumping level below land surfaces: 18.25 ft. after 1 hrs. pumping 510 g.p.m. 18.7 ft. after 4 hrs. pumping 510 g.p.m. Estimated maximum yield 700 g.p.m.																								
			13. Water sample submitted: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date																								
			14. Well head completion: <input type="checkbox"/> Pitless adapter 30 inches above grade																								
			15. Well grouted? Yes With: <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.																								
			16. Nearest source of possible contamination: 500 ft. Direction SW Type River Well disinfected upon completion? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No																								
			17. Pump: <input type="checkbox"/> Not installed Manufacturer's name Layne & Bowler Model number LORKEH HP 60 Volts 460 Length of drop pipe 30 ft. capacity 550 g.p.m. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other																								
			(Use a second sheet if needed)																								
18. Elevation: Topography: <input type="checkbox"/> Hill <input type="checkbox"/> Slope <input type="checkbox"/> Upland <input checked="" type="checkbox"/> Valley		19. Remarks:		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Layne Western Co. 102 Business name License No. Address Wichita, Kansas Signed Layne Western Co. 102 Date 5/1/79 Authorized representative																							

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5