

1 LOCATION OF WATER WELL: County: Riley	Fraction *See below NW 1/4 NW 1/4 SE 1/4	Section Number 14	Township Number T 11 S	Range Number R 06 EW
--	---	----------------------	---------------------------	-------------------------

Distance and direction from nearest town or city street address of well if located within city?

Southeast corner of B St. & Second St. Camp Sunston Ft. Riley, KS 1044MW95-8

2 WATER WELL OWNER: US Army Corps of Engineers

RR#, St. Address, Box # : 601 E 12th St.

City, State, ZIP Code : Kansas City, MO 64106

Board of Agriculture, Division of Water Resource

Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: N W E S	4 DEPTH OF COMPLETED WELL: 32.5 ft. ELEVATION: 1059.7868 TC Depth(s) Groundwater Encountered 1. 24.3 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr 9/14/95 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 10.5 in. to 32.5 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No
--	--

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS Blank casing diameter 2 in. to 31.5 ft. Dia. in. to ft. Dia. in. to ft. Casing height above land surface 2 in., weight Flush Mount Cover lbs./ft. Wall thickness or gauge No. SCH 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 3 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 16 ft. to 31 ft. From ft. to ft. GRAVEL PACK INTERVALS: From 15 ft. to 31.5 ft. From ft. to ft.	CASING JOINTS: Glued Clamped Welded Threaded X
---	--

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Concrete surface to 3.5 Grout Intervals: From 3.5 ft. to 13 ft. From 13 ft. to 15 ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage UST site
--

Direction from well?		How many feet?	
FROM	TO	LITHOLOGIC LOG	PLUGGING INTERVALS
0	8"	Concrete	
8"	3.5'	Dark Brown Silty w/Gravel	
3.5'	24'	Brown Silty Clay	
24'	32.5'	Sand	
		Location referenced to Ft. Riley Datum	
		281002.13161 N	
		2357835.58346 E	
		1059.7868 Elev.	

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9/14/95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 510 This Water Well Record was completed on (mo/day/yr) 1-2-96 under the business name of MIKON Corporation by (signature) Paul Brian
