

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:	Fraction NW ¼	SE ¼	SW ¼	Section Number 12	T 11 S	Range Number R 6 E/W	
Distance and direction from nearest town or city street address of well if located within city?							
POL Site 1245, Ft. Riley Army Base							
2 WATER WELL OWNER:	US Army DPW-Environmental Div. 404 Pershing Court Fort Riley, KS 66442			Board of Agriculture, Division of Water Resources Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:							
4 DEPTH OF COMPLETED WELL	30.5	ft. ELEVATION:					
Depth(s) Groundwater Encountered	1	ft. 2	ft. 3	ft.			
WELL'S STATIC WATER LEVEL	ft. below land surface measured on mo/day/yr						
Pump test data: Well water was NA . . . ft. after hours pumping gpm							
Est. Yield . . . NA . . . gpm:	Well water was ft. after hours pumping gpm						
Bore Hole Diameter 8 . . . in. to 30.5 . . . ft. and in. to ft.							
WELL WATER TO BE USED AS:	5 Public water supply	8 Air conditioning	11 Injection well				
1 Domestic	3 Feedlot	6 Oil field water supply	9 Dewatering				
2 Irrigation	4 Industrial	7 Lawn and garden only	10 Monitoring well				
Was a chemical/bacteriological sample submitted to Department? Yes No ✓; If yes, mo/day/yr sample was submitted							
Water Well Disinfected? Yes No ✓							
5 TYPE OF BLANK CASING USED:	1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped		
	2 PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded		
Blank casing diameter 1 . . . in. to 15.5 . . . ft. Dia in. to ft. Dia in. to ft.	Threaded. ✓						
Casing height above land surface -0.5 . . . in., weight lbs./ft. Wall thickness or gauge No. . . . Sch. 40 . . .							
TYPE OF SCREEN OR PERFORATION MATERIAL	7 PVC	10 Asbestos-cement					
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)			
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)				
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes				
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)				
SCREEN-PERFORATED INTERVALS: From 15.5 . . . ft. to 30.5 . . . ft. From ft. to ft.							
From ft. to ft. From ft. to ft. From ft. to ft.							
GRAVEL PACK INTERVALS: From 13 . . . ft. to 30.5 . . . ft. From ft. to ft.							
From ft. to ft. From ft. to ft. From ft. to ft.							
6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other			
Grout Intervals: From ft. to 9 . . . ft. From 9 . . . ft. to 13 . . . ft. From ft. to ft.							
What is the nearest source of possible contamination:							
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well			
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well			
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)			
Direction from well?							
FROM	TO	LITHOLOGIC LOG		FROM	TO	PLUGGING INTERVALS	
0	4	Clay, lean (CL), Dark Brown					
4	16	Sand, fine (SP), Brownish Gray					
16	20	As above, fine to med.,					
20	30	Sand, fine (SP), Gray					
							PZ-2 POL Site 1245
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9/25/2009 and this record is true to the best of my knowledge and belief.							
Kansas Water Well Contractor's License No. . . . 527 This Water Well Record was completed on (mo/day/yr) 11/17/09							
under the business name of GeoCore, Inc.	by (signature) <i>John R. Lee</i>						
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.							