

[1] LOCATION OF WATER WELL:		Fraction	Township Number	Range Number	
County: Riley	Fraction: SW ¼ SE ¼ SW ¼	Section Number: 12	Township Number: T 11 S	Range Number: R 6 E/W	
Distance and direction from nearest town or city street address of well if located within city? POL Site 1245, Ft. Riley Army Base					
[2] WATER WELL OWNER: US Army DPW-Environmental Div. RR#, St. Address, Box # : 404 Pershing Court City, State, ZIP Code : Fort Riley, KS 66442		Board of Agriculture, Division of Water Resources Application Number:			
[3] LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		[4] DEPTH OF COMPLETED WELL 30.5 . . . ft. ELEVATION: Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr Pump test data: Well water was NA ft. after hours pumping gpm Est. Yield NA gpm; Well water was ft. after hours pumping gpm Bore Hole Diameter 11 in. to 32 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Extraction well Was a chemical/bacteriological sample submitted to Department? Yes No ✓ ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No ✓			
[5] TYPE OF BLANK CASING USED:					
(1) Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped	
2 PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded	
		7 Fiberglass		Threaded. ✓	
Blank casing diameter 4 . . . in. to 15.5 . . . ft. Dia . . . in. to . . . ft. Dia . . . in. to . . . ft.					
Casing height above land surface . . . -0.5 . . . in.; weight . . . lbs./ft. Wall thickness or gauge No. Sch. 40 SS.					
TYPE OF SCREEN OR PERFORATION MATERIAL					
1 Steel	(3) Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)	
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot	(3) Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)	
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes		
		7 Torch cut	10 Other (specify)		
SCREEN-PERFORATED INTERVALS: From 15.5 ft. to 30.5 ft. From ft. to ft. From ft. to ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 13 ft. to 32 ft. From ft. to ft. From ft. to ft. From ft. to ft.					
[6] GROUT MATERIAL: (1) Neat cement 2 Cement grout (3) Bentonite 4 Other					
Grout Intervals: From 4.5 ft. to 8 ft. From 8 ft. to 13 ft. From ft. to ft.					
What is the nearest source of possible contamination?					
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well	
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well	
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)	
Direction from well? How many feet?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4	Clay, lean (CL), Dark Brown			
4	16	Sand, fine (SP), Brownish Gray			
16	20	Sand, fine to med.,			Lat = 39.103228
20	30	Sand, med. (SP), Gray			Long = -96.719867
					WGS 84
					DPE17 POL Site 1245
[7] CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9/29/2009 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 12/13/09 by signature Dan Kohl under the business name of GeoCore, Inc.					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					