

1 LOCATION OF WATER WELL:		Fraction *See Below		Section Number		Township Number		Range Number	
County: Riley		NE 1/4 NW 1/4 NW 1/4		24		T 11 S		R 6 EW	
Distance and direction from nearest town or city street address of well if located within city?									
TS0392-2 ±200' E of Fourth & M Street, Camp Funston, Ft. Riley, Kansas									
2 WATER WELL OWNER: U.S. Army Corps of Engineers									
RR#, St. Address, Box # : 601 East 12th Street									
City, State, ZIP Code : Kansas City, Missouri 64106									
Board of Agriculture, Division of Water Resources									
Application Number:									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 32 ft. ELEVATION: 1051.3							
		Depth(s) Groundwater Encountered 1. 26 ft. 2. ft. 3. ft.							
		WELL'S STATIC WATER LEVEL 17.7 ft. below land surface measured on mo/day/yr							
		Pump test data: Well water was ft. after hours pumping gpm							
		Est. Yield gpm: Well water was ft. after hours pumping gpm							
		Bore Hole Diameter 11 in. to 33.5 ft. and in. to ft.							
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well							
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)							
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well							
		Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted							
		Water Well Disinfected? Yes No X							
5 TYPE OF BLANK CASING USED:									
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped									
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded									
Blank casing diameter 2 in. to 33.5 ft. Dia. in. to ft. Dia. in. to ft.									
Casing height above land surface 24 in. weight lbs./ft. Wall thickness or gauge No. Sch 40									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement									
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)									
12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)									
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes									
10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From 31.5 ft. to 21.5 ft. From ft. to ft.									
GRAVEL PACK INTERVALS: From 33.5 ft. to 19 ft. From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Bentonite Pellets 19'-17'									
Grout Intervals: From 17 ft. to 3.5 ft. From ft. to Concrete ft. From 3.5 ft. to 0 ft.									
What is the nearest source of possible contamination:									
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well									
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)									
13 Insecticide storage UST Site									
Direction from well? How many feet?									
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS									
0 26.5 Gray Silty Clay									
26.5 33.5 Gray Coarse Sand w/Gravel									
*Location referenced to Ft. Riley Datum									
283,069 N									
2,363,303.3 E									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12/7/92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 510 This Water Well Record was completed on (mo/day/yr) 3/24/93 under the business name of MIKON Corporation by (signature) David J. Keamer									