

1 LOCATION OF WATER WELL:	Fraction *See Below	Section Number	Township Number	Range Number
County: Riley	NE 1/4 NW 1/4 NW 1/4	28	T 11 S	R 6 E/W

Distance and direction from nearest town or city street address of well if located within city?

TS0392-1 ±700' S of Seventh & L Street, Camp Funston, Ft. Riley, Kansas

2 WATER WELL OWNER: U.S. Army Corps of Engineers	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # : 601 East 12th Street	Application Number:
City, State, ZIP Code : Kansas City, Missouri 64106	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 20.5 ft. ELEVATION: 1045.7
	Depth(s) Groundwater Encountered 1. 15 ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 14.3 ft. below land surface measured on mo/day/yr
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter 11 in. to 22 ft., and in. to ft.
WELL WATER TO BE USED AS:	
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted	
Water Well Disinfected? Yes No X	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Threaded X
Blank casing diameter 2 in. to 20.5 ft., Dia in. to ft., Dia in. to ft.			
Casing height above land surface 0 in., weight lbs./ft. Wall thickness or gauge No. Sch. 40			
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless steel	5 Fiberglass	7 PVC
2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped	8 Saw cut
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:		From 20 ft. to 10 ft.	From ft. to ft.
GRAVEL PACK INTERVALS:		From 22 ft. to 8 ft.	From ft. to ft.

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other Bentonite Pellets 8'-6'
Grout Intervals: From 6 ft. to 3.5 ft.	From ft. to Concrete ft.	From 3.5 ft. to 0 ft.		
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	UST Site
Direction from well?			How many feet?	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	0.8	Concrete			
0.8	11	Dark Brown Clay			
11	22	Gray Medium to Coarse Sand			
		*Location referenced to Ft. Riley Datum			
		281,105.2 N			
		2,363,622 E			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12/4/92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 510 This Water Well Record was completed on (mo/day/yr) 3/24/93 under the business name of MIKON Corporation by (signature) David J. Kemer
--