

1 LOCATION OF WATER WELL: County: Riley	Fraction * See Below NE 1/4 NW 1/4 NW 1/4	Section Number 24	Township Number T 11 S	Range Number R 6 E/W
--	--	----------------------	---------------------------	-------------------------

Distance and direction from nearest town or city street address of well if located within city?

TS0492-4 ±200' N of Second &amp; B Street, Camp Funston, Ft. Riley, Kansas

2 WATER WELL OWNER: U.S. Army Corps of Engineers RR#, St. Address, Box # : 601 East 12th Street City, State, ZIP Code : Kansas City, Missouri 64106	Board of Agriculture, Division of Water Resources Application Number:
---	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 33.5 ft. ELEVATION: 1061.1
--	---

Depth(s) Groundwater Encountered 1. 28 ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL 28.0 ft. below land surface measured on mo/day/yr

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 11 in. to 36 ft., and in. to ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	7 Lawn and garden only
		10 Monitoring well

12 Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes No ☒ X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No ☒ X

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
------------------------------	----------------	-----------------	------------------------------

1 Steel

☒ 2 PVC

3 RMP (SR)

4 ABS

Blank casing diameter 2 in. to 33.5 ft., Dia in. to ft., Dia in. to ft.

Casing height above land surface in., weight lbs./ft. Wall thickness or gauge No. Sch 40

6 Asbestos-Cement

7 Fiberglass

9 Other (specify below)

Welded

Threaded ☒ X

TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement
---	-------	--------------------

1 Steel

2 Brass

3 Stainless steel

4 Galvanized steel

5 Fiberglass

6 Concrete tile

8 RMP (SR)

9 ABS

11 Other (specify)

12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot

☒ 3 Mill slot

2 Louvered shutter

4 Key punched

5 Gauzed wrapped

6 Wire wrapped

7 Torch cut

8 Saw cut

9 Drilled holes

10 Other (specify)

11 None (open hole)

SCREEN-PERFORATED INTERVALS:	From 33 ft. to 23 ft.	From ft. to ft.
------------------------------	-----------------------	-----------------

GRAVEL PACK INTERVALS:	From 36 ft. to 20.8 ft.	From ft. to ft.
------------------------	-------------------------	-----------------

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other Bentonite Pellets 20.8'-18.2'
-------------------	---------------	----------------	-------------	---------------------------------------

Grout Intervals: From 18.2 ft. to 3.5 ft., From Concrete ft., From 3.5 ft. to 0 ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	UST Site

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	26	Gray to Gray Brown Silty Clay			
26	33.3	Brown Medium Sand			
33.3	34.3	Gray Silt			
34.3	34.8	Gravelly Sand			
34.8	35.8	Gray Silt			
35.8	36	Gravelly Sand			
		*Location referenced to Ft. Riley Datum			
		281,279.6 N			
		2,358,182.5 E			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12/8/92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 510 This Water Well Record was completed on (mo/day/yr) 3/24/93 under the business name of MIKON Corporation by (signature) David J. Kramer
---