L,			\// A T.E	R WELL RECOR	D Form WWC-5	KSA 82a-1	212			
	ON OF WATE		Fraction		Se	ction Number	Township N		Range N	
County:	R dispolan fro	iley	SE ½ town or city street add	SW 1/4	NW 1/4	1	T 11	S	R /	E
				2850 West 32	2 ^{na} Ave., Manha	attan, KS				
2 WATER	WELL OWNE	R: Kan	sas State Unive	ersity Attn:	Kelly Greene					
RR#. St. Ac	dress, Box #	: 108	Edwards Hall				Board of Agri	culture, Divis	sion of Water	Resources
City. State.	ZIP Code	: Mar	hattan, KS 665	05			Application N	umber:		
LOCATE	E WELL'S LOC N SECTION B	CATON WI	T 1 1 1 1		=u 3	0 ft ELEV	/ATION:	10	34.65	
JAN A II	N SECTION E	OA.	Depth(s) Ground	water Encounter	ed 15 2	4.5 ft	. 2	ft. ;	3	Ft.
A [ı	WELL'S STATIC	WATER LEVEL	ed 1.5 2 25.31 f	t. below land s	urface measured	on mo/day/y	r 08/2	9/13
	NW _ _	NE	Pump	test data: We	ell water was	F	t. after	hours p	umping	Gpm
	\mathbf{x}	-	Est. Yield	Gpm: We	ell water was	F	t. after	Hours p	umping	Gpm
₩ W -			E Bore Hole Diame	ter 8.5	In. to	30	ft. and	in.	to	Ft.
	0.47		WELL WATER T	O BE USED AS	In. to 5 Public water 6 Oil field water	supply	8 Air condition	ning 11	Injection we Other (Spec	ll :ifv below)
-	SW	_ SE	2 Irrigation	4 Industrial	7 Lawn and ga	rden (domesti	c) 10 Monitorin	n well	MW-	. 7
+ L					ample submitted to					
	S		Submitted	Jacter lological S	ample submitted to		iter Well Disinfect			
5 TVDE O	F BLANK CAS	SING USE		5 Wrought Ir	on 8 Cond					
1 Ste			MP (SR)		Cement 9 Othe			Welde		
2 PV		7 4 AB	• •	7 Fiberglass		(-)	,	Threa	ided	X
- Inneren				Et .						
Blank casin	g diameter _	2	in. to 20	Dia	In	. to	ft., Dia		in. to	ft.
			FLUSH	In., weight	SCH 40	Lbs./ft.	Wall thickness o	r gauge No.		
			TION MATERIAL: ainless steel	5 Eiborgloog		A	10 Asb 11 Oth			
1 Ste			ainless steel alvanized steel			ABS	12 Nor	e used (ope	n hole)	
			NINGS ARE:		Gauzed wrapped		8 Saw cut			en hole)
	ntinuous slot		3 Mill slot	6	Wire wrapped		9 Drilled holes			
			4 Key punched		Torch cut		10 Other (spec	cify)		
SCREEN-P	ERFORATED	INTERVA			30					
			From	ft, to	20	ft. f	rom	it. to)	
1AS	ND PACK INT	ERVALS:			30					
			From	ft. to			-1 Other		9	
6 GROUT	MATERIAL:	1 Ne	Santharia dipenin	Cement grout Ft.	[3 Bt	entonite	4 Other			
Grout Interv	als From2	0.5	ft. to 16	From3	16 to	18	ft. From		ft. to	ft.
What is the	nearest sourc	e of possil	ble contamination:				tock pens		andoned wate	
	ptic tank		4 Lateral lines		Pit privy	11 Fuel	•	Hart Control of the Party of th	well/ Gas well	
	wer lines		5 Cess pool		Sewage lagoon		izer storage	-	er (specify be ntaminate	
	tertight sewer	lines	6 Seepage pit	9 F	eedyard	13 Insec	ticide storage	COI	ntaniniate	a Site
Direction fro	TO	CODE	LITHOL	OGIC LOG	FROM			UGGING IN	ITERVALS	
0	1		Topsoil	0010 200		, , , , ,				
1	24		Silty Clay							
24	30		Limestone Gra						-	
30	TD		End of Borehol	е						
							.,	, ,	· · · · · · · · · · · · · · · · · · ·	
· · · · · · · · · · · · · · · · · · ·										
	<u> </u>	-								
				011 77		-1-1 (0)	material (C)	ماريمود يا ا	lor mu ludadi	tion and
7 CONTR	ACTOR'S OR	LANDOW	NER'S CERTIFICATI 08/2	ON: This water	well was (x) const					
Completed	on (mo/day/yı	")	U8/Z	585	And		true to the best of ecord was comple			
Water Well	Contractor's l	License No). Δecociat	ed Environ	mental, Inc.	vvalei vveli Ki	ecoro was comple By (signature) B	radlev .l	Johnson	7/17/17/1 A
INSTR	usiness name UCTIONS:, Pl	ease fill in b	lanks and circle the corr	ect answers. Ser	nd three copies to Ka	nsas Departme	nt of Health and En	iroment, B	eau of Vater	Topeka,
Kansas	s 66620-0001.	Telephone:	913-296-5545. Send	one to WATER W	ELL OWNER and re	tain one for you	r records.`	Mach	1/gh	
									11	