

1 LOCATION OF WATER WELL: County: Riley Fraction: SE 1/4 SE 1/4 SE 1/4 Section Number: 1 Township Number: T 11 S Range Number: R 7 E

Distance and direction from nearest town or city street address of well if located within city? 5 1/2 miles south on Meadow Creek

2 WATER WELL OWNER: Clarence Swallon
 RR#, St. Address, Box #: 3800 Meadow Creek Rd
 City, State, ZIP Code: Marion, KS 66502

Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 50 ft. ELEVATION: 30 ft.

Depth(s) Groundwater Encountered 1. 30 ft. 2. 30 ft. 3. 30 ft.

WELL'S STATIC WATER LEVEL 30 ft. below land surface measured on mo/day/yr

Pump test data: Well water was 100 gpm: Well water was 10 in. to 10 ft., and 10 in. to 10 ft.

Est. Yield 100 gpm: Well water was 10 ft. after 10 hours pumping 100 gpm

Bore Hole Diameter 10 in. to 10 ft., and 10 in. to 10 ft.

WELL WATER TO BE USED AS:

1 Domestic	3 Feedlot	5 Public water supply	8 Air conditioning	11 Injection well
2 Irrigation	4 Industrial	6 Oil field water supply	9 Dewatering	12 Other (Specify below)
7 Lawn and garden only 10 Monitoring well				

Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted No

Water Well Disinfected: Yes No

5 TYPE OF BLANK CASING USED:

1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: <u>Glued</u>
2 PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below)	<u>Clamped</u>
				<u>Welded</u>
				<u>Threaded</u>

Blank casing diameter 5 in. to 30 ft., Dia. 5 in. to 30 ft., Dia. 5 in. to 30 ft.

Casing height above land surface 2 in., weight 50 lbs./ft. Wall thickness or gauge No. 40

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify)
				12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
				10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 30 ft. to 50 ft., From 30 ft. to 50 ft., From 30 ft. to 50 ft.

GRAVEL PACK INTERVALS: From 20 ft. to 50 ft., From 20 ft. to 50 ft., From 20 ft. to 50 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Bentonite

Grout Intervals: From 0 ft. to 20 ft., From 20 ft. to 50 ft., From 50 ft. to 50 ft.

What is the nearest source of possible contamination: Non Close

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	11	Brown Clay			
11	30	Sandy Clay			
30	38	Gravel and clay (Water)			
38	50	Coarse Sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4/26/89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 457 This Water Well Record was completed on (mo/day/yr) 5/29/89 under the business name of Craig Haldeman Well Drilling by (signature) Craig Haldeman