

1) LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: RILEY		NW ¼ NE ¼ NW ¼	7	T 11 S	R 8 E/W
Distance and direction from nearest town or city street address of well if located within city? 4 south of Manhattan					
2) WATER WELL OWNER: Wilbur R. Erichsen RR#, St. Address, Box # : 3150 McDowell Creek Rd. City, State, ZIP Code : Manhattan, KS 66502					
Board of Agriculture, Division of Water Resources Application Number:					
3) LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4) DEPTH OF COMPLETED WELL: 80' ft. ELEVATION:				
	Depth(s) Groundwater Encountered 1... 42' ft. 2... ft. 3... ft.				
	WELL'S STATIC WATER LEVEL ... 27' ft. below land surface measured on mo/day/yr ... 11-12-92				
	Pump test data: Well water was ft. after hours pumping gpm				
	Est. Yield .8..... gpm: Well water was ft. after hours pumping gpm				
	Bore Hole Diameter .8 3/4...in. toft., andin. toft.				
WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes.....No...X.....; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No					
5) TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped + 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 5" in. to ... 0-40 ft., Dia ... 5" in. to ... 50-79 ft., Dia in. to ft. Casing height above land surface 24" in., weight 2.82 lbs./ft. Wall thickness or gauge No. 258 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 40 ft. to 50 ft., From ft. to ft. From 79 ft. to 80 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 24 ft. to 80 ft., From ft. to ft. From ft. to ft., From ft. to ft.					
6) GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? north How many feet? 130'					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Top Soil			
2	38	Clay-Brown			
38	42	Cherty Limestone-Yellow-Loose			
42	50	Shale-Yellow			
50	80	Shale-Grey			
7) CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-12-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 182 This Water Well Record was completed on (mo/day/yr) 12-7-92 under the business name of STRADER DRILLING CO., INC. by (signature) Dale Erichsen					