WATER WELL RECORD	Form WWC-5	Division of Water Resou	
1 LOCATION OF WATER WELL:	Fraction	Section Number Town	
County: NA BALLS DC	14 NW NE 1/4 NE 1/4		S R 3 DE □W
Street/Rural Address of Well Location; i		Global Positioning Syste	
from nearest town or intersection: If at o	owner's address, check here \mathcal{L} .		(in decimal degrees)
			(in decimal degrees)
		Elevation:	
2 WATER WELL OWNER:) 50 P.	Watson	Collection Method:	NAD 83, NAD 27
RR#, Street Address, Box #:	y Watson Re		el:)
City, State, ZIP Code : Digital Map/Photo, Topographic Map, Land Surv			
Tole ks. 666/5 Est. Accuracy: 3 m, 3-5 m, 5-15 m			
3 LOCATE WELL	Plugged		ana hacas
WITH AN "X" IN 4 DEPTH OF 6			
	N WELL'S STATIC WATER LEVEL 1t. below land surface measured on mo/day/yr		
WELL STATIC WATER EL VELLIMONALITIE OF WIND AND AND AND AND AND AND AND AND AND A			
FOR VIELD 7	ECT VIELD A water was A offer hours numning com		
NW NE EST. TIELD.			
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well			
Demostic Desides Doil field water symply Developing Downtoning Cheer (Specify below)			
SW SE Domestic Feedlot Oli field water supply Dewatering Other (Specify below) Irrigation Industrial Domestic-lawn & garden Monitoring well Clased Aco. P			
Was a chemical/bacteriological sample submitted to Department? Yes No			
S If yes, mo/day/yr sample was submitted			
1 mile Water well disinfected? ☐ Yes ☑ No			
5 TYPE OF CASING USED: Steel PVC N Other H. D. Polyethylege.			
5 TYPE OF CASING USED: Steel PVC Other .H. D Colyethylene. CASING JOINTS: Glued Clamped Welded Threaded Fus:			
Casing diameter			
Casing height Alexand surface			
TYPE OF SCREEN OR PERFORATION MATERIAL:			
Steel Stainless Steel PVC Other (Specify)			
Brass Galvanized Steel None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE: Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)			
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)			
SCREEN-PERFORATED INTERVALS: From			
From ft. to ft., From ft. to ft.			
			ft. to ft.
From ft. to ft., From ft. to ft.			
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other			
Grout Intervals: From			
What is the nearest source of possible contamination: Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)			
Septic tank			
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well			
Direction from well		from well	•••••
FROM TO LITHOLOG	IC LOG FROM	TO LITHO. LOG (co	ont.) or PLUGGING INTERVALS
0 2 50:1+clay	120	148 line	
2 29 500dstone	148	154 Shale	200 -3
29 31 lime 31 38 Shale 38 45 line 45 92 sandy Shale 92 94 line	1,54	162 line	
31 38 Shale	162	169 Shale	13 200' Bores Plugged
38 45 line	169		With High Soliday
45 92 sandy Shall	174	200 Shale	Beatonite
92 96 line			
96 100 Shale			
106 108 line			
108 100 Shale	US CEDITIEICATION. This was	ton yyoll yyog 🔽 constmusted	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was a constructed, or plugged under my jurisdiction and was completed on (mo/day/year)			
Kansas Water Well Contractor's License No			
under the business name of Evans Energy Dev Inc. by (signature)			
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies			
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.			
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at			
http://www.kdheks.gov/waterwell/index.html. KSA 82a-1212			
INCIA CAM INIA			