WATER WELL RECORD		Form WV	VC-5	Div	vision of Wate	r Resources App. N	0.	
1 LOCATION OF WATER WELL: County: Shawnee		Fraction NE 1/4 NE 1/4 NE	14 NE 14	Section	n Number 1	Township No. T 12 S	Range Number R 14  ZE  W	
	dress of Well Location; i		Global Positioning System (GPS) information:					
from nearest town or intersection: If at owner's address, check here .					Latitude: .39.04083(in decimal degrees)			
Southwest corner of the Indian Hills Rd. and Huntoon St.				Longitude: 95.79934 (in decimal degrees)				
Intersection					Elevation: .1082			
					Datum: WGS 84, NAD 83, NAD 27			
2 WATER WELL OWNER: Groundsource Inc. RR#, Street Address, Box #: 216 E. 5th				Collec	Collection Method:  ☐ GPS unit (Make/Model: Garmin)			
City, State, ZIP Code : Holton, KS 66436				☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey				
	HOILOII, I	NS 00430	Est. Accuracy:					
3 LOCATE WELL								
WITH AN "X" II								
SECTION BOX:	Depth(s) Groundwater Encountered (1).NA							
	1 1							
I I DOT VIELD DO W-II NA A A A NA I							ping. IXA gpin	
NWNE- W	Bore Hole Diame	eter 6 in to 1	6					
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well								
SW   SE -	│	Feedlot C	Dil field wate	er supply	/ De	ewatering	Other (Specify below)	
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well Geothermal								
		bacteriological sample				Yes 🗹 No		
S If yes, mo/day/yr sample was submitted								
Water well disinfected? ☐ Yes ☑ No								
5 TYPE OF CASING USED: Steel PVC Other HDPE								
CASING JOINTS: Glued Clamped Welded Threaded								
Casing diameter .3/4 in. to .143 ft., Diameter .na								
Casing height above land surface. below 48 in., Weight								
TYPE OF SCREEN OR PERFORATION MATERIAL:  Steel Stainless Steel PVC Other (Specify)								
Brass Galvanized Steel None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:								
☐ Continuous slot ☐ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)								
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)								
SCREEN-PERFORATED INTERVALS:         From								
GRAVEL PACK INTERVALS: From NA ft. to ft., From ft. to ft.								
From								
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other								
Grout Intervals:	From .4 ft. to	ft., From		ft. to	ft.,	From	ft. toft.	
What is the nearest source of possible contamination:								
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☑ Other (specify below) ☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well								
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well house								
	vell north							
FROM TO	LITHOLOG	IC LOG	FROM	TO	LITHO. L	OG (cont.) or PLU	JGGING INTERVALS	
	clay, brown		117	143	Shale, gra	У		
	imestone							
	hale, Gray				V-10-7.			
	imestone						WILL.	
	hale, Gray				6 holes to	143 feet bas		
	imestone					12 A S. 12 A S		
	hale, Gray							
	imestone							
	hale, Gray			,	,		***************************************	
113   117   Limestone								
under my jurisdiction and was completed on (mo/day/year) .7/15/09								
Kansas Water Well Contractor's License No. 760. This Water Well Record was completed on (production) 9/1/09								
under the business name of Associated Drilling, Inc. by (signature)								
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies								
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include <u>fee</u> of \$5.00 for each <u>constructed</u> well. Visit us at								
http://www.kdheks.gov/waterwell/index.html.								
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy								