


1 LOCATION OF WATER WELL: County: Shawnee	Fraction NW 1/4 NE 1/4 NE 1/4	Section Number 7	Township Number T 12 S	Range Number R 15 EW
--	----------------------------------	---------------------	---------------------------	-------------------------

Distance and direction from nearest town or city street address of well if located within city?

22nd. & Topeka Blvd., Topeka, KS. 66611

2 WATER WELL OWNER: Steve Nollar RR#, St. Address, Box #: 2245 S. Topeka City, State, ZIP Code: Topeka, KS. 66612	Board of Agriculture, Division of Water Resources Application Number:
---	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 19' ft. ELEVATION: Depth(s) Groundwater Encountered 1. 19' ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 8.31 ft. below land surface measured on mo/day/yr 6/21/95 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8 1/2" to 4" ft., and 5 1/2" in. to 19" ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X
---	---

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X Blank casing diameter 2.375 in. to 3' ft., Dia in. to ft., Dia in. to SDR 13 ft. Casing height above land surface Flush Mt. in., weight lbs./ft. Wall thickness or gauge No. SCH 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 18' ft. to 31' ft., From ft. to ft. GRAVEL PACK INTERVALS: From 19' ft. to 2 1/2' ft., From ft. to ft. From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 2 1/2' ft. to 1 1/2' ft., From 1 1/2' ft. to 0' ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fertilizer storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? East How many feet? 30'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	.75	Asphalt			
.75	4	Mustard yellow brn-yellow gray weathered shale, dry, no odor.			
4	5	Bedrock limestone			
5	10.25	Interbedded limestone & shale layers 6" thick.			
10.25	15	Gray shale, dry, no odor.			
15	18	Interbedded limestone-shales.			
18	19	Limestone-hard.			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-20-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 539 This Water Well Record was completed on (mo/day/yr) 6-21-95 under the business name of JB Environmental Drilling by (signature) James Becker
--