


1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Shawnee		NW 1/4 NE 1/4 NE 1/4	7	T 12 S	R 15 EW
Distance and direction from nearest town or city street address of well if located within city?					
22nd. & Topeka Blvd., Topeka, KS. 66611					
2 WATER WELL OWNER: Steve Nollar		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box #: 2245 S. Topeka		Application Number:			
City, State, ZIP Code: Topeka, KS. 66612					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 25' ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 16.63 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 16.63 ft. below land surface measured on mo/day/yr 6-21-95			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm; Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 8 1/2 in. to 8' ft., and 5 1/2 in. to 25' ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile		Welded X			
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below)		Threaded			
Blank casing diameter 2.375 in. to 4' ft., Dia in. to SDR 13 ft.					
Casing height above land surface Flush Mt. in., weight lbs./ft. Wall thickness or gauge No. SCH 40					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 24' ft. to 4' ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 25' ft. to 3 1/2' ft. From ft. to ft.					
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other			
Grout Intervals: From 3 1/2 ft. to 2 1/2 ft. From 2 1/2 ft. to 0' ft. From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage					
Direction from well? North		How many feet? 75-80'			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	.50	Asphalt			
.50	8	Olive gray-yellow gray shaley clay to shale, moist, no odor.			
8	9	Limestone			
9	12	yellow shale, dry to moist, no odor.			
12	14	Interbedded limestones & shales.			
14	15	Gray shale, dry, no odor.			
15	18.50	Limestone			
18.50	23	Gray shale, dry, no odor.			
23	24	Limestone			
24	25	Gray shale, dry.			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-19-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 539 This Water Well Record was completed on (mo/day/yr) 6-21-95 under the business name of JB Environmental Drilling by (signature) James Becker					