


1 LOCATION OF WATER WELL: Fraction NE 1/4 NW 1/4 NE 1/4 Section Number 12 Township Number T 12 S Range Number R 15 E
 County: Shawnee

Distance and direction from nearest town or city street address of well if located within city?
1201 SW 21st Street, Topeka, Ks.

2 WATER WELL OWNER: Tom Haag
 RR#, St. Address, Box #: 7233 SE 85th Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Auburn, KS. 66402 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 15.50 ft. ELEVATION:
 Depth(s) Groundwater Encountered: 1.90 ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL: 10.4 ft. below land surface measured on mo/day/yr 1-29-96
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield gpm: Well water was ft. after hours pumping gpm
 Bore Hole Diameter: 8 1/2 in. to 9 ft., and 5 1/2 in. to 15 1/2 ft.
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
2 PVC 4 ABS 7 Fiberglass Threaded X
 Blank casing diameter: 2.375 in. to 5 ft., Dia in. to ft., Dia in. to SDR 13 ft.
 Casing height above land surface: Flush Mt. in., weight lbs./ft. Wall thickness or gauge No. SCH 40
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 11 Other (specify)
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 15' ft. to 5' ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 15' ft. to 4' ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 4' to 3' ft., From 3' to 0' ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 1 Fuel storage Fuel 15 Oil well/Gas well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage
 Direction from well? East How many feet? 150'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	.75	Asphalt			
.75	3	Dk brn clay, moist to dry, firm, low plasticity, no odor.			
3	9	Med brn mottled clay w/ oxide staining, moist to dry, no odor, oxide stringers.			
9	14	Weathered limestone layers, hard, dry, fractured, tan-chalky, no odor.			
14	15.50	Gray shale, dry, no odor, friable.			

*FH OK'd by Don Taylor
 Waiver sent in previous w/ final set of well for this site*

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-29-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 539 This Water Well Record was completed on (mo/day/yr) 2-7-96 under the business name of JB Environmental Drilling by (signature) James Baker

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4