WATER WELL RECORD	Form WWC-5	Division of Water Resources App. No.
1 LOCATION OF WATER WELL:	Fraction	Section Number Township No. Range Number
County: Shawnee	1/4 NE 1/4 NE 1/4 NE 1/4	9 T 12 S R 15 ZE W
Street/Rural Address of Well Location; i from nearest town or intersection: If at o		Global Positioning System (GPS) information:  Latitude: .39,0287.17
	owner's address, check here [_].	Longitude: 95.744283 (in decimal degrees)
Former Amoco Station No. 1929 2101 SW Fairlawn Road, Topeka, KS 66614		Elevation: 1003
		<u>Datum</u> : ☐ WGS 84, <b>☑</b> NAD 83, ☐ NAD 27
	ducts North America	Collection Method:  GPS unit (Make/Model:)
and a state of the	forch Parkway	☐ GPS umt (Make/Model:) ☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey
vvarrenv	ville, IL 60555	Est. Accuracy: <b>Z</b> <3 m, <b>3-5</b> m, <b>5-15</b> m, >15 m
3 LOCATE WELL	30	Δ.
WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL 30 ft. Depth(s) Groundwater Encountered (1).21 ft. (2).N/A ft. (3).N/A ft.		
SECTION BOX:  N  Depth(s) Groundwater Encountered (1).21		
Pump test data: Well water was N/Aft. after N/A hours pumping N/A gpm		
EST. YIELD N/Agpm. Well water was N/Aft. after N/A hours pumping N/Agpm		
W		
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well		
SWSE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)    Irrigation   Industrial Domestic-lawn & garden   Monitoring well MW-8R		
Was a chemical/bacteriological sample submitted to Department? Yes V No		
s If yes, mo/day/yr sample was submitted. N/a		
Water well disin	fected? Yes No	
5 TYPE OF CASING USED: Steel V PVC Other		
CASING IOINTS: Gland G Clamped Welded V Threaded		
Casing diameter 2 in to 15 ft. Diameter N/A in to N/A ft. Diameter N/A in to N/A ft.		
Casing height above land surface. U. in., Weight N/A. lbs./ft., Wall thickness or gauge No. Schedule 40		
TYPE OF SCREEN OR PERFORATION MATERIAL:		
☐ Steel ☐ Stainless Steel ☐ Brass ☐ Galvanized Steel	✓ PVC [ None used (onen hole)	Other (Specify)
Brass Galvanized Steel None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:		
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)		
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)		
SCREEN-PERFORATED INTERVALS: From 15 ft. to 30 ft., From N/A ft. to N/A ft.		
GRAVEL PACK INTERVALS: From 13 ft. to 30 ft., From N/A ft. to N/A ft.		
	From N/A ft. to N/A	ft. From .N/A ft. to .N/A ft.
6 GROUT MATERIAL: ☐ Neat cement		
Grout Intervals: From .2		
What is the nearest source of possible contamination:    Septic tank		
Septic tank Lateral lin Sewer lines Cesspool	nes Pit privy Divestoch Sewage lagoon Fuel store	
☐ Watertight sewer lines ☐ Seepage 1	oit 🔲 Feedyard 🔲 Fertilizer	storage Oil well/gas well
Direction from well East		e from well . <50-feet
FROM TO LITHOLOG		TO LITHO. LOG (cont.) or PLUGGING INTERVALS
3 0.5 Conside 2 mfacts	(XIII)	
0.5 6 pin at silar of	as -30-6 breef 10	
(0 10 red-bry 52)	1/18 20x x26 2/10	
O oxfo c Medium	THE BY NO IS	
10 13 weathered de	red-pero	
Sorteno		
13 30 ch red-bin	s Gadstone	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was a constructed, reconstructed, or plugged		
under my jurisdiction and was completed on (mo/day/year) .8-18-2014		
under the business name of RAZEK Environmental, LLC by (signature)		
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send one copy to		
Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.  Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at		
http://www.kdheks.gov/waterwell/index.html		