OW#	8		WATER	WELL RECORD	Form WWC-	5 KSA 82	2a-1212			
1 LOCATIO	N OF WAT	ER WELL:	Fraction		Se	ction Numbe		ber	Range Number	
County:	Shawnee		NE 1/4	NE 1/4]	NE 1/4	9	T 12	s	R 15 (E) X	
Distance and direction from nearest town or city street address of well if located within city?										
21st & Fairlawn, Topeka, Kansas										
2 WATER	WELL OW								'	
2 WATER WELL OWNER: Amoco 0il Company RR#, St. Address, Box # 8700 Indian Creek Parkway Board of Agriculture, Division of Water Resources										
City, State,		0,00 1							IVISION OF VValer Resources	
1			nd Park, l		20.0					
AN "X"	N SECTION									
		1 De							ft.	
Ŧ	!!!	x W							5/8/90	
Pump test data: Well water was ft. after hours pumping gpm										
	Est. Yield gpm: Well water was hours pumping gpm									
	Bore Hole Diameter 6 in to 30 ft and in to ft									
* w -	1			BE USED AS:			8 Air conditioning		ī	
-	- 1	i	1 Domestic	3 Feedlot			9 Dewatering		I	
	- SW	SE	2 Irrigation	4 Industrial						
1 1	! !	' wa	•						mo/day/yr sample was sub-	
<u> </u>	<u>'</u>			cteriological sample	Submitted to t	•		-		
EL 7005 0	5 51 4444 6		tted				Vater Well Disinfected?		No x	
		ASING USED:		5 Wrought iron					Clamped	
1 Stee		3 RMP (SR)		6 Asbestos-Cement		` '	•		d	
<u>2 PVC</u> 4 ABS 7 Fiberglass										
Blank casing diameter 2 in. to 5 ft., Dia in. to ft. Dia in. to ft. Dia in. to ft. Dia in. to SCU 4.0 in. to SCU 4.0 in. to SCU 4.0 in. to selection of the sel										
Casing heigh	ght above la	ınd surface	81.'i	s., weight		Ibs	s./ft. Wall thickness or g	gauge No	SCU . 4.0	
TYPE OF S	SCREEN O	R PERFORATION M	MATERIAL:		7 P'	/C	10 Asbest	os-cemer	nt	
1 Stee	el	3 Stainless st	eel	5 Fiberglass	8 R	MP (SR)	11 Other	(specify) .		
2 Bras	ss	4 Galvanized	steel	6 Concrete tile	9 A		12 None	used (ope	en hole)	
SCREEN O	R PERFOR	RATION OPENINGS			zed wrapped		8 Saw cut	` '	11 None (open hole)	
				6 Wire wrapped			9 Drilled holes		(0,000,000,000,000,000,000,000,000,000,	
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 5 ft. to 29 ft., From ft. to ft. to										
From										
_									1	
G	HAVEL PA	CK INTERVALS:								
		T	From	ft. to			om		ft.	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other										
Grout Intervals: From										
What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well										
1 Sep	otic tank	4 Lateral li	nes 7 Pit privy 11 Fu			el storage 15 Oil well/Gas well				
2 Sev	ver lines	5 Cess po				12 Fert	12 Fertilizer storage 16 Other (specify below)			
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage										
Direction fro	-	northea	•	,			any feet? 50			
FROM	ТО		LITHOLOGIC L	OG	FROM	TO		GING IN	TERVALS	
0	5"	Topsoil				30'	bottom of bo	ring		
5"	7.8'		lean clay	, brown, fir	m					
	7.0			gravel, trac						
			a. 4 , Sa	nd lens at 7	• /					
		to 7.7'				ļ				
7.81	11'			athered, oli						
		gray, (very	y fine to	fine grained		<u> </u>				
		angular to	subangula	r sand, < 25%						
		silt, < 20%								
11'	30 '			, tan brown						
		with trace								
		grained, ar		•						
		_	•	_						
				e), becoming						
				ale lens at						
19.5 to 21', becoming moist at 26.5',										
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was										
completed of	on (mo/day/	year) 3/29/	90			and this red	cord is true to the best		wledge and belief. Kansas	
Water Well	Contractor's	s License No	.416	This Water \	Well Record w	as completed	d on (mo/day/ <u>yr</u>)	5/.9	/90	
under the b			acon Const			by (sign	, (10)	\mathcal{S}_{\sim}	mley	
					Please fill in blank		rcle the correct answers. Send	top three co	opies to Naneas Department	
							OWNER and retain one for v			