


1 LOCATION OF WATER WELL: Fraction SW 1/4 SW 1/4 SW 1/4 Section Number 10 Township Number T 12 S Range Number R 15 E/W
 County: SHAWNEE

Distance and direction from nearest town or city street address of well if located within city?
NE COR. OF INTER. OF 29TH AND FAIRLAWN, TOPEKA

2 WATER WELL OWNER: THOMAS BINKLEY
 RR#, St. Address, Box #: 2219 SW TERRACE #24 Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: TOPEKA, KS, 66611 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 21.23 ft. ELEVATION: 947.18
 Depth(s) Groundwater Encountered 1. 14.8 ft. 2. — ft. 3. — ft.
 WELL'S STATIC WATER LEVEL 12.2 ft. below land surface measured on mo/day/yr 07-06-92
 Pump test data: Well water was — ft. after — hours pumping — gpm
 Est. Yield 7.25 gpm: Well water was — ft. after — hours pumping — gpm
 Bore Hole Diameter 1.1 in. to 19.8 ft., and 2 in. to 21.8 ft.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes — No X; If yes, mo/day/yr sample was submitted —
 Water Well Disinfected? Yes — No X

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued — Clamped: —
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded —
2 PVC 4 ABS 7 Fiberglass Threaded X
 Blank casing diameter 2 in. to 21.23 ft., Dia — in. to — ft., Dia — in. to — ft.
 Casing height above land surface 19 in., weight 5.4 lbs./ft. Wall thickness or gauge No. —
 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) —
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes —
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) —
 SCREEN-PERFORATED INTERVALS: From 11.23 ft. to 21.23 ft., From — ft. to — ft.
 From — ft. to — ft., From — ft. to — ft.
 GRAVEL PACK INTERVALS: From GR 11.23 ft. to 21.23 ft., From — ft. to — ft.
 From — ft. to — ft., From — ft. to — ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other —
 Grout intervals: From 6L ft. to 11.23 ft., From — ft. to — ft., From — ft. to — ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage CONTAMINATED
 Direction from well? — How many feet? —

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4	TOP SOIL			
4	2.5	BACK FILL - CLAY SILTY-SCAT. LIMESTONE + CHERT GRAVEL			
2.5	5.0	CLAY - DK GREY			
5.0	8.2	CLAY - SILTY - GREY			
8.2	10.8	SILTY CLAY			
10.8	15.8	CLAY SILTY - GREEN TAN. STRONG ODOB - GAS - WATER			
15.8	19.8	CLAY SILTY - GREY			
19.8	21.8	TIGHT - MOIST - SILTY CLAY			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 06-29-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 4 This Water Well Record was completed on (mo/day/yr) 07-26-92 under the business name of EBBERTS DRILLING by (signature) Gregory Ebberts

OFFICE USE ONLY
T
R
EW
SEC.
1/4
1/4
1/4