


1 LOCATION OF WATER WELL: Fraction SW 1/4 SW 1/4 SW 1/4 Section Number 10 Township Number T 12 S Range Number R 15 EW  
 County: SHAWNEE

Distance and direction from nearest town or city street address of well if located within city?  
NE COR IF INTER OF 29TH AND FAIRLAUN - TOPEKA

2 WATER WELL OWNER: THOMAS BINKLEY  
 RR#, St. Address, Box #: 2219 SW TERRACE # 24 Board of Agriculture, Division of Water Resources  
 City, State, ZIP Code: TOPEKA, KS 66611 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  
  
 4 DEPTH OF COMPLETED WELL: 16.8 ft. ELEVATION: 943.80  
 Depth(s) Groundwater Encountered 1. 14.2 ft. 2.        ft. 3.        ft.  
 WELL'S STATIC WATER LEVEL 9.85 ft. below land surface measured on mo/day/yr 07-01-92  
 Pump test data: Well water was        ft. after        hours pumping        gpm  
 Est. Yield        gpm: Well water was        ft. after        hours pumping        gpm  
 Bore Hole Diameter 1.1 in. to 16.8 ft. and        in. to        ft.  
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well  
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well SAMP-TEST  
 Was a chemical/bacteriological sample submitted to Department? Yes        No X; If yes, mo/day/yr sample was submitted         
 Water Well Disinfected? Yes        No X

5 TYPE OF BLANK CASING USED: NA  
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued        Clamped         
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded         
 7 Fiberglass Threaded         
 Blank casing diameter NA in. to        ft., Dia        in. to        ft., Dia        in. to        ft.  
 Casing height above land surface        in., weight        lbs./ft. Wall thickness or gauge No.         
 TYPE OF SCREEN OR PERFORATION MATERIAL: NA  
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement  
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)         
 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE: NA  
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
 7 Torch cut 10 Other (specify)         
 SCREEN-PERFORATED INTERVALS: From NA ft. to        ft., From        ft. to        ft., From        ft. to        ft.  
 GRAVEL PACK INTERVALS: From NA ft. to        ft., From        ft. to        ft., From        ft. to        ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other         
 Grout Intervals: From 3 ft. to 16.8 ft., From        ft. to        ft., From        ft. to        ft.  
 What is the nearest source of possible contamination:  
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
CONTAMINATED  
 Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	.5	FILL - LS + GRAVEL - CLAY	3	16.8	NEAT CEMENT
.5	5.2	CLAY - DK. GRAY.			
5.2	11.2	CLAY - SILT - TAN - BR. STAINS			
11.2	16.8	CLAY - DRK GRAY - SILTY			
	12.3	STRONG GAS BUBBL			
	14.2	H2O -			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 07-01-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 479 This Water Well Record was completed on (mo/day/yr) 07-26-92 under the business name of EBBERTS DRILLING by (signature) Jugan Ebberts

OFFICE USE ONLY  
T  
R  
EW  
SEC.  
1/4  
1/4  
1/4