USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

Couldn't find

## WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors)

	L. S			Topeka, Kansas 66620
County	Fraction Secti		number	Township number Range number 10 10
1. Location of well: 514wwee	SE 1/4 SE 1/4 SE 1	/4 2	.0	1 /2 (5) R +5 (DW
2. Distance and direction from nearest town or city: 2 5 oF  R.R. or street: 2735				4 yerring Ton 5 Ashworth Pl
4. Locate with "X" in section below: Sketch map:				6. Bore hole dia. 3 in. Completion date Well depth 160 ft. 6-19-79
				Well depth 160 ft. 6-14-14
NW NE X				7 Cable tool Rotary Driven Dug Hollow rod Jetted Bored Reverse rotary
1 1 1 E	200'			8. Use: Domestic Public supply Industry
₩				Irrigation Air conditioning Stock Lawn Oil field water Other
SW SE X SEPTIC	/			9. Casing: Material File Height: Above or below
1 1				Threaded
1 Mile			Τ΄	Dia 5 in. to 200ft, depth Wall Thickness; inches or Dia in. to ft. depth gage No. 253
5. Type and color of material		From	То	10 Screen: Manufacturer's name
Top Soll		0	6	Type PVC Dia. 5
Clay brown		6		610 gauze 1020 Length 30
4			14	Set between
Shale grey		14	52	Gravel pack? Size range of material 4 X / 8
Lime grey		52	57	11. Static water level:  110 ft. below land surface Date 6-19-79
shale gray		57	79	12. Pumping level below land surfaces: ft. after hrs. pumping g.p.m.
Limestone, grey, shaley		79	112	ft. after hrs. pumping g.p.m.
Shola shu				Estimated maximum yield g.p.m.  13. Water sample submitted: mo./day/yr.
3.17164 14724	4	1/2		Yes No Date
SANd STONE, WATER bean.	ng		141.	14. Well head completion: 14. Well head completion: 14. Well head completion: 14. Well head completion: 15. Well head comp
Shale grey	A Company of the Comp	191	160	15. Well grouted?
				With: Neat cement Bentonite Concrete Depth: From ft. to ft.
				16. Nearest source of possible contamination: SppTIL
				ft. 200 Direction Sw Type Spp No
	No. All Control of the Control of th			17. Pump:  Manufacturer's name JACUZZI
	****			Model number .554 A HP 1/2 Volts 230
				Length of drop pipe <u>150</u> ft. capacity <u>5</u> g.p.m.
				Submersible Turbine
(Use a second s	heet if needed)			
18. Elevation: 19. Remarks:				20. Water well contractor's certification:
ewalt to ins	Tail Slab			This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Topography:	<i>w</i> . – <i>w</i>			STRAder Dalg Co Inc 182.   Business name License No.
Slope				Address RTI Hollon, ITS
Upland Valley				Signed Authorized representative Date 6-20-19