


mw-1

1 LOCATION OF WATER WELL: County: Shawnee Fraction: NW 1/4 NE 1/4 NE 1/4 Section Number: 14 Township Number: T 12 S Range Number: R 15 EW

Distance and direction from nearest town or city street address of well if located within city?
2525 W 29th, Topeka, Kansas

2 WATER WELL OWNER: Coastal Mart Attn: Hugh Bostic
 RR#, St. Address, Box #: 110 S. Main #500
 City, State, ZIP Code: Wichita, Kansas 67202
 Board of Agriculture, Division of Water Resources
 Application Number: 919.23

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX



4 DEPTH OF COMPLETED WELL: 20.0' ft. ELEVATION: 919.23
 Depth(s) Groundwater Encountered: 1. 15.0' ft. 2. — ft. 3. — ft.
 WELL'S STATIC WATER LEVEL: 15.05' ft. below land surface measured on mo/day/yr 9/16/94
 Pump test data: Well water was — ft. after — hours pumping — gpm
 Est. Yield — gpm: Well water was — ft. after — hours pumping — gpm
 Bore Hole Diameter: 8.625 in. to 20' ft., and — in. to — ft.
 WELL WATER TO BE USED AS:
 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well mw-1
 Was a chemical/bacteriological sample submitted to Department? Yes — No X; If yes, mo/day/yr sample was submitted —
 Water Well Disinfected? Yes — No X

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded —
2 PVC 4 ABS 7 Fiberglass Threaded X
 Blank casing diameter: 2" in. to 10' ft. Dia. — in. to — ft. Dia. — in. to — ft.
 Casing height above land surface: Flush in. weight Schedule 40 lbs./ft. Wall thickness or gauge No. —
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) —
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) —
 SCREEN-PERFORATED INTERVALS: From 10' ft. to 20' ft. From — ft. to — ft.
 From — ft. to — ft. From — ft. to — ft.
 SAND GRAVEL PACK INTERVALS: From 9.0 ft. to 20' ft. From — ft. to — ft.
 From — ft. to — ft. From — ft. to — ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other —
 Grout Intervals: 3 ft. to 7.0' ft. From 3 ft. to 9.0' ft. From — ft. to — ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage 16 Other (specify below)
contaminated site
 Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
GL	1	Concrete underlain by fill sand			
1	3	silty clay, gray above PL			
3	5.5	clayey silt, dk gray, soft			
5.5	15.5	silty clay, gray firm			
15.5	17.0	silty clay, yellow-tan			
17.0	20.0	shale			
20.0	TD				

FLUSH MOUNT WAIVER
 09-07-94
 RICHARD HARPER

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 09-12-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 479 This Water Well Record was completed on (mo/day/yr) 10-10-94 under the business name of EBBERTS DRILLING by (signature) Alroya Ebberts