	WATI	ER WELL RECORD	Form WWC-5	KSA 82	a-1212		mw.	#6
1 LOCATION OF WATER WELL:	Fraction			n Number	Township N	lumber	Range Nu	ımber
County: Sawnee		4 56 1/4 5	E 1/4	<u> </u>	T 12	S	R 15	E/W
Distance and direction from nearest				0. 1	-11	1	1.0	
North of corner	of Sw.	29th st a	nd SW 1	Kand	olph, Iz	ope Ka	i, Ks	
2) WATER WELL OWNER: CH			6. Schell		. ,	'		
		sas Ave K					Division of Wate	r Resource
City, State, ZIP Code : 7		KS 666				n Number:		
LOCATE WELL'S LOCATION WIT AN "X" IN SECTION BOX:			22.0					
AN A IN SECTION BOX.	1	dwater Encountered					01 1 1 -	
7	WELL'S STATK	C WATER LEVEL .!	6.4.1 ft. belo	w land su	ırface measured or	n mo/day/yr	7/16/94	L
NW NF	1	np test data: Well wa						
	i	gpm: Well wa						
× ! !	Bore Hole Diam	neter , <b>8. 6</b> 25in. t	0 22	ft.,	and		. to	
<u>₹</u> "	WELL WATER	TO BE USED AS:	5 Public water s		8 Air conditioning	-	Injection well	
1   SW  SF	1 Domestic		6 Oil field water		9 Dewatering			
	2 Irrigation				Monitoring we			
	Was a chemical	l/bacteriological sample	e submitted to Depa	artment?	/esNo	; If yes	, mo/day/yr sam	ple was su
\$	mitted			W	ater Well Disinfecte	ed? Yes -	- No	Χ
5 TYPE OF BLANK CASING USED	<b>)</b> :	5 Wrought iron	8 Concrete	tile	CASING JO	INTS: Glue	d Clamp	ed
1 Steel 3 RMP	(SR)	6 Asbestos-Cemen	t 9 Other (sp	ecify belo	ow)		ed <del></del>	
2)PVC 4 ABS	100	7 Fiberglass	<del></del>	<b>.</b>			aded 🗶	
_	in. to 12.0	'	in. to					
Casing height above land surface	FIUSH	in., weight <b>5<i>Cl</i>.</b>		lbs	/ft. Wall thickness	or gauge N	o	
TYPE OF SCREEN OR PERFORAT	ION MATERIAL:		(7)PVC		10 As	bestos-ceme	ent	
1 Steel 3 Staint	less steel	5 Fiberglass	8 RMP	(SR)	11 Oth	ner (specify)	<del></del>	
2 Brass 4 Galva	anized steel	6 Concrete tile	9 ABS		12 No	ne used (op	en hole)	
SCREEN OR PERFORATION OPEN	INGS ARE:	5 Gai	uzed wrapped		8 Saw cut		11 None (ope	n hole)
1 Continuous slot	Mill slot	6 Wir	e wrapped		9 Drilled holes			
2 Louvered shutter 4	Key punched	7 Tord	22. o		10 Other (specif	y) <del></del> .		
Grout Intervals: From G.L What is the nearest source of possit	From at cement tt. to 9.0	ft. to  ft. to  cernent grout  ft., From	9 3Bentoniti	ft., Fro e 4 . //	Other	ft. t	o ft. to bandoned water	
	ateral lines	7 Pit privy			storage	$\sim$	il well/Gas well	
	ess pool	8 Sewage la	agoon		lizer storage		ther (specify be	
3 Watertight sewer lines 6 Se	epage pit	9 Feedyard			cticide storage	COM	aminate	
Direction from well? FROM TO	LITHOLOGIC	1.00			any feet?	LUGGING I		te
GL 1.0 Soil,			FROM	то		LUGGING	NICHVALS	
	Silty Cla	Thelens OI		i				
8.0 14.0 Clave	inty, proun	rown above I	0,					
14.0 18.0 Sandy	gravely	Class						
18.0 22.0 Shale	Jhlung	y bold la	-,- <del> </del>					
22.8 TD	., billegra	y, hald, dr	7     .					
22.0 10								
	INCH MAN	CATT WINITE	170					
	19-17	-64	- 1					
77	MARADA	INT WAIDE 1-94 HARPER						
	ICH PICO	MANIEN						
								÷
7 CONTRACTOR'S OR LANDOWN	IER'S CERTIFICAT	ION: This water well						
	09-14-9	•			ord is true to the be			ief. Kansa
Water Well Contractor's License No.	7.79	This Water	Well Record was o	completed	on (mo/day/yr) .	10-1	0-94	
under the business name of	BBERTS	DRILLI	NG	by (signa	ature)	ogans	best	1000
INSTRUCTIONS: Use typewriter or ball po of Health and Environment, Bureau of Wa								partment