	WATER	WELL RECORD F	orm WWC-5	KSA 82a-	.1919		M	UI A	+4	
1 LOCATION OF WATER WELL:	Fraction	WELL HEOOND 1	-	n Number	, 	Number	F	Range Nu	mber	
County: SHAWNEE	NE 1/4	NW ME	1/4	0	T /3	2 s	R	16	Æ W	
Distance and direction from nearest town	4 .							, v		
1224 S.KANSAS A	AVE.	TODEKA	KAN	SAS						
2 WATER WELL OWNER: TOWN & COUNTRY										
RR#, St. Address, Box # Board of Agriculture, Division of Water Resources										
City, State, ZIP Code :PO 50)	(17087	LUICHITA,	KANSAL	s cotd	/ Applica	tion Number:				
3 LOCATE WELL'S LOCATION WITH 4	DEPTH OF CO	MPLETED WELL	8.5	ft. ELEVAT	TION:					
AN "X" IN SECTION BOX:										
Depth(s) Groundwater Encountered										
Pump test data: Well water was ft. after hours pumping gpm										
	Est. Yield gpm: Well water was									
	Bore Hole Diameter 7.74 in. to 8.5 ft., and in. to in. to ft.									
1.5 W	WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well									
T	1 Domestic	3 Feedlot 6	Oil field water	r supply	9 Dewatering	12	Other ((Specify b	elow)	
	2 Irrigation				Monitoring v			· · · · · · · · · · · · · · · · · · ·		
	Vas a chemical/ba	cteriological sample su	-	•						
Y S n	nitted			Wat	er Well Disinfe	ected? Yes		No		
5 TYPE OF BLANK CASING USED:		5 Wrought iron	8 Concrete	e tile	CASING	JOINTS: Glue	ed	Clampe	∍d	
1 Steel 3 RMP (SR)		6 Asbestos-Cement	9 Other (s	pecify below	()	Wel	ded			
PVC 4 ABS		7 Fiberglass				Thre	eaded.X			
Blank casing diameter ir	1. to	ft., Dia ,	in. to .		ft., Dia		. in. to		ft.	
Casing height above land surface		/ /								
TYPE OF SCREEN OR PERFORATION			O PVC			Asbestos-cem				
1 Steel 3 Stainless s	steel	5 Fiberglass	8 RMP	(SR)	11 (Other (specify	/)			
2 Brass 4 Galvanized		6 Concrete tile	9 ABS	` ,		12 None used (open hole)				
SCREEN OR PERFORATION OPENING	S ARE:	5 Gauzed	wrapped		8 Saw cut	11 None (open hole)				
1 Continuous slot (3)Mill slot 6 Wire wro			apped		9 Drilled hole	es			·	
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)										
SCREEN-PERFORATED INTERVALS: From										
From										
GRAVEL PACK INTERVALS:	From & r.~	<i>S ft. to</i>	3,5	ft., From	n <i></i>	ft.	to		ft.	
	From	ft. to		ft., Fron			to		ft.	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other										
Grout Intervals: From 3ft	:. to 	ft., From	ft. to	5	ft., From	.	ft. f	to		
What is the nearest source of possible co	ontamination:			10 Livest	ock pens	14	Abandor	ned water	well	
1 Septic tank 4 Lateral lines 7 Pit priv		7 Pit privy		Fuel storage			15 Oil well/Gas well			
2 Sewer lines 5 Cess p	ool	8 Sewage lagoo	n	12 Fertilizer storage			16 Other (specify below)			
3 Watertight sewer lines 6 Seepag	ge pit	9 Feedyard		13 Insect	cicide storage					
Direction from well? W25+				How man	ny feet?	o'				
FROM TO	LITHOLOGIC LO	OG	FROM	то		PLUGGING	INTERV	/ALS		
0 05 CONCRE	te									
0.5 5 BJACK W/W. 5 8.5 FAT Clay,	ood Frengmi	ents & brick								
5 8.5 FAT CLAY,	BROWN	TO TAN				. , ,				
						- 1199				
7 CONTRACTOR'S OR LANDOWNER'S	S CERTIFICATIO	N: This water well was	(/T) constructe	ed, (2) recor	nstructed, or (3) plugged ur	nder mv	jurisdictio	n and was	
completed on (mo/day/year)	21-95		16 /		rd is true to the					
Water Well Contractor's License No. 5.75 This Water Well Record was completed on (mo/day) 8.77.95										
under the business name of KUETZ	ENVIRONI		VICE	by (signate	7111	[][
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Sand top three copies to Kansas Department										
of Health and Environment, Bureau of Water, To									ļ	