	WATE	ER WELL RECORD	Form WW	C-5 KS	A 82a-	1212 ID	No				
1 LOCATION OF WATER WELL:				1 '.				Number Range Number			
	SE 1/4					Т	12	S	R	16	Ε
Distance and direction from nearest to 2061 SE California Ave, Topel		dress of well if loc	ated within ci	ty?							
2 WATER WELL OWNER: Chevr		ental Manage	ement Co	mpany							
RR#, St. Address, Box # : PO Bo		entai manag		inpany		Poor	of Agrico	alterno Dire	isian of M	latar Bass	
City, State, ZIP Code : <b>Bellai</b>	re TX 77401						•		ISION OF VV	ater Reso	urces
LOCATE WELL'S LOCATON WITH	ie, ix 77401					Аррис	ation Nu	mber:			
AN "X" IN SECTION BOX:	DEPTH OF C	COMPLETED WEL	L	<b>19.25</b> f	t. ELE	VATION:		967	.49 (TO	C)	
1		water Encountere									ft.
NW NE	WELL'S STATIC	WATER LEVEL		ft. belov	v land	surface me	asured o	n mo/day/	'yr		•
		o test data: Well									
₩ W		gpm: Well									
	Bore Hole Diame	eter <b>8</b> in	n. to	19.25		ft. and		ir	to		ft
sw	WELL WATER T	eter <b>8</b> in O BE USED AS: : 3 Feed lot	5 Public wa	ater supply		8 Air	condition	ing 1	1 Injectio	n well	''.
	1 Domestic	3 Feed lot	6 Oil field v	vater suppl	y	9 De	watering	1	2 Other (	Specify be	low)
+ <u>i i x</u>	2 Irrigation	4 Industrial	7 Lawn and	d garden (d	iomest	ic) 10 M	onitoring	well	<b></b>		
S	Was a chemical/	bacteriological sar	mple submitte	ed to Depar	tment?	Yes	No X	If yes	mo/day/v	r sample v	was
	submitted	•	•	·		ater Well D				No X	
5 TYPE OF BLANK CASING USED:		5 Wrought Iron	n 8 (	Concrete tile							
1 Steel 3 RMP	(SR)	6 Asbestos-Ce						Weld		. S.c.iipou	
2 PVC 4 ABS	. ,	_		` `	•	,				Flush	
		7 Fiberglass		·				Threa			
Blank casing diameter 2	in. to 4.2	tt., Dia	0.702	_ in. to		tt., Dia			in. to		ft.
Casing height above land surface F		in., weight	0.703	T =		Wall thick				SCH. 40	
TYPE OF SCREEN OR PERFORATIO				7 PVC							
		5 Fiberglass		8 RMP	(SR)		11 Other	(specify)		. <b></b>	
2 Brass 4 Galva SCREEN OR PERFORATION OPENIN	nized steel	6 Concrete tile	e Gauzed wrap	9 ABS		0 60	12 None	used (ope	en hole)	n (anan ha	la\
	Mill slot		Wire wrappe				ed holes		II None	e (open no	ie)
	Key punched		Torch cut					5.4)			
	, ,				4	10 Othe	er (specii	y)	· · · · · · · · · · · · · · · · · · ·		
SCREEN-PERFORATED INTERVALS	: From	4.25 ft. to		.25	n.	-rom		π. τ	0	·	- π.
	From	ft. to	40	25	π.	rom		n. t	۰		tt.
GRAVEL PACK INTERVALS:		3.25 ft. to		.25							
	From	ft. to			ft.			ft. t			ft.
GROUT MATERIAL: 1 Neat		_			_	4 Other					
Grout Intervals From 1	ft. to 3.25	ft. From		ft. to		ft.	From		ft. to		ft.
What is the nearest source of possible	contamination:					stock pens			andoned v	vater well	
1 Septic tank	4 Lateral lines	7 Pit				storage			well/ Gas		
2 Sewer lines	5 Cess pool		wage lagoon			izer storag		16 Oth	er (specif	fy below)	
3 Watertight sewer lines	6 Seepage pit	9 Fee	edyard			ticide store	age				
Direction from well?	LITUOL	0010100			v many	feet?					
FROM TO CODE  O 1 As	phait and Gr	OGIC LOG	FR	OM -	то		PLU	GGING IN	HERVAL	5	
	ty Clay, brown		to								
	nt brown	. to dark brown	.5								
	nestone										
15.5 19 Mu	dstone, brow	n									
	nestone										
7 CONTRACTORIS OF LANDOWS	DIS CEDTIES ATS	ONI. This waster	11	a a turi a turi	201 :		(0)			41-41	
7 CONTRACTOR'S OR LANDOWNE											
completed on (mo/day/yr)	10/12			nd this reco							
Nater Well Contractor's License No.		531		his Water \	Well Re	ecord was	com/plete	d on (mo/	day/yr)	10/19/	07
under the business name of		al Services Ir		by (sign	ature)	1 by	165				
INSTRUCTIONS:. Please fill in blank Jackson St., Ste. 420, Topeka, Kansa	s and circle the corress 66612-1367. Tele	ect answers. Send t phone: 913-296-55	hree copies to 45. Send one	Kansas Der to WATER	partmer WELL (	it of Health	and Environ	onment, Bu e for your r	reau of Wa ecords.	ater, 1000 S	W