				ATER WELL RECORD				212 ID No.				
	ON OF WATE					Section N			ip Number	Ran	ge Numb	er
	Sha		SE		SE ¼			т 1	2 s	R	16	E
	nd direction fro California			et address of well if loo	cated within city	?						
				nmental Manag	ement Con	npany						
	dress, Box #			g				Board of	Agriculture, Divi	sion of Wa	oter Res	ources
City State	7ID Code	· Bell:	aire TX 774	01				Applicatio	n Number:			
LOCATE	E WELL'S LO	CATON WI	TH 4					7 (ppilodilo	irramber.			
JAN "X"	N SECTION E	BOX:	DEPTH (OF COMPLETED WE	LL	9.5 ft	. ELEV	ATION:	969.	39 (TO	<u>C)</u>	
1			Departs, or	andwater Encountere	,	·	'		'\.			' (
-	n'w 	NE		ATIC WATER LEVEL								
<u>u</u>	i	i	_ F	ump test data: Wel	l water was		ft.	after	hours p	umping	-	gpm
₹ W -		-	Est. Yield	gpm: Wel	water was		ft.	after	hours p	umping		gpm
		-	Bore Hole Di	ameter 8 in ER TO BE USED AS: estic 3 Feed lot	n. to	19.5		ft. and	in	. to		ft.
	SW †-	SE	1 Dome	estic 3 Feed lot	6 Oil field water	er supply ter supply	v	9 Dewate	aitioning 11 erina 12	i injection 2 Other (S	n well Specify b	elow)
↓		X		tion 4 Industrial						2 01.101 (0	, poo, b	0.017
	S		1	ical/bacteriological sa								
			submitted	icai/bacteriological sa								was
5 TYPE O	F BLANK CAS	CINC LICE		5 Wrought Iro	· · · · · · · · · · · · · · · · · · ·				ected? Yes		No X	
				6 Asbestos-C					JOINTS: Glued Weld		Clamped	'···
		4 ABS	, ,				•	ſ			Eluci	
2 PV				7 Fiberglass						led		
Blank casin	g diameter		in. to	4.5 ft., Dia	0.702	n. to		ft., Dia		in. to		
				it in., weight					s or gauge No. Asbestos-ceme		CH. 40	
1 Ste			ION MATERIAL: inless steel									1
2 Bra			vanized steel	5 Fiberglass 6 Concrete tile	Α.	9 ARS	(SK)	12 1	None used (ope	n hole)		
			INGS ARE:		Gauzed wrappe				toric asea (ope		(open h	ole)
1 Co	ntinuous slot	Γ	3 Mill slot	6	Wire wrapped			9 Drilled h			(-	,
2 Lou	vered shutter	, -	4 Key punched	7	Torch cut			10 Other (s	pecify)			
SCREEN-P	ERFORATED	INTERVAL	S: From	4.5 ft. to	19.	5	ft. Fr	om	ft. to)		ft.
				ft. to					ft. to			
GR	AVEL PACK I	NTERVALS		^ -	19.	5	ft. Fr	om	ft. to)		ft.
			From						ft. to			ft.
6 GROUT	MATERIAL:	1 Nea	at cement	2 Cement grout	3 8	Bentonite] 4	1 Other				
				.5 ft. From		t. to	•		m			ft.
			e contamination:					ck pens		indoned w	ater well	
1 Sep	otic tank		4 Lateral lin	ies 7 Pit	privy	11	Fuel st	orage	15 Oil	well/ Gas	well	
2 Sev	wer lines		5 Cess poo	l 8 Se	wage lagoon	12	Fertiliz	er storage	16 Oth	er (specify	below)	
	tertight sewer	lines	6 Seepage	pit 9 Fe	edyard	13	Insection	cide storage				
Direction fro		LOODE		101.0010.1.00			many fe	eet?	B			
FROM 0	10 1	CODE	Sphalt and	HOLOGIC LOG	FRO	M 1	0		PLUGGING IN	TERVALS	<u> </u>	
1	12.5			rk brown to brown					···········			
12.5	14.25		imestone									
14.25	15		Mudstone, or	range-brown								
15	16		imestone									
16	19		Mudstone, b	rown to gray								
19	19.5	<u> </u>	imestone									
7 CONTRA	CTOR'S OR	LANDOWN	ER'S CERTIFIC	ATION: This water we	ell was (1) cons	ructed, (2	2) recons	structed, or (3) plugged under	my jurisd	iction and	was
completed o	n (mo/day/yr)		10)/12/07	and	this reco	ord is tru	e to the best	of pay knowledg	ge and bel	ief. Kan	sas
	Contractor's L			531				71	pleted on (mo/o			
under the bu	siness name	of	Geotechi	nical Services I	nc.	by (signa	ature)	1/2 /	4			
INSTRU	JCTIONS: Ple	ase fill in bla	nks and circle the	correct answers. Send	three copies to K	ansas Dep	artment	of Health and	Environment, Bur	eau of Wa	ter, 1000	s w