WATER WELL RECORD	Form WWC-5	Di	vision of Wate	r Resources App. N	Jo. L	
1 LOCATION OF WATER WELL: County: Shawee	Fraction NW/4 NW 1/45LW 1/4 SL	Section Section	on Number	Township No.	Range Number R L VE □W	
Street/Rural Address of Well Location; if unknown, distance & direction Global Positioning System (GPS) information:						
from nearest town or intersection: If at	ያ. Latitι	atitude: (in decimal degrees)				
			Longitude: (in decimal degrees)			
			Elevation:			
2 WATER WELL OWNER:		Datun	<u>n</u> : U WGS 84	4, 📘 NAD 83, 🗀	] NAD 27	
DRU Street Address Day 4. CVA OI 430 CIOON Concetton Method.						
City State ZIP Code 5748 36 Collaboration Topographic Man Digital Man/Photo Digital						
Berry	tan, KS, 66409	Est. A			] 5-15 m,	
3 LOCATE WELL	ompleted well	۸_ ۵				
WITH AN "X" IN 4 DEPTH OF	GOMPLETED WELL		ft.	3.200	00162	
SECTION BOX: Depth(s) Ground	Depth(s) Groundwater Encountered (1). None. ft. (2)					
WELL'S SIAT	N WELL'S STATIC WATER LEVEL No. 2ft. below land surface measured on mo/day/yr					
ECT VIELD W	ECT VIELD Water was Wall water was ft offen have anyoning					
NWNE EST. HELD.						
	WELL WATER TO BE USED AS: ☐ Public water supply ☐ Geothermal ☐ Injection well					
	Irrigation   Industrial   Domestic-lawn & garden   Monitoring well .C.!o.Sect100.β					
Was a chemical/bacteriological sample submitted to Department? Yes No						
S If yes, mo/day/yr sample was submitted						
Water well disin	fected? 🗌 Yes 🕟 No					
5 TYPE OF CASING USED: Steel PVC V Other H.D. Polyethylene						
5 TYPE OF CASING USED: Steel PVC Other H.D. Polyethy lene CASING JOINTS: Glued Clamped Welded Threaded Fusion						
Casing diameter 31.4 in. to 200 ft., Diameter in. to ft., Diameter ft.						
Casing height and surface						
TYPE OF SCREEN OR PERFORATION MATERIAL: No.						
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)						
Brass Galvanized Steel None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE: None (open hole)						
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)						
SCREEN-PERFORATED INTERVALS: From						
From ft. to ft., From ft. to ft.						
GRAVEL PACK INTERVALS: From						
From ft. to ft., From ft. to ft.						
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other						
Grout Intervals: FromQ.O ft. to						
What is the nearest source of possible contamination:						
Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well					ther (specify below)	
Watertight sewer lines Seepage pit Feedyard Fertilizer sto			Oil well/ga			
Direction from well		ince from w	) 2 mm € 1			
FROM TO LITHOLOG				OG (cont.) or PL	UGGING INTERVALS	
0 15 Sail+clay						
15 19 Sands toxe						
19 22 lime						
22 25 Shale						
25 38 line	200	3	3-200	bores pl	lugged with	
38 1/6 Shale			High	Solid Bo	entonite	
116 /35 line			J		•	
135 179 Shale						
179 182 line						
182 200 State					- Processing -	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged						
under my jurisdiction and was completed on (mo/day/year)						
Kansas Water Well Contractor's License No. 56.1 This Water Well Record was completed on (mo/day/year) 3.5.1						
under the business name of Evans Engray Dev. Inc. by (signature) by (signature).  INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies						
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.						
Telephone 785-296-5522. Send one copy to WAT						