

LOCATION OF WATER WELL: County: SHAWNEE Fraction: SW 1/4 SW 1/4 NW 1/4 Section Number: 33 Township Number: T 12 S Range Number: R 16 E/W

Distance and direction from nearest town or city street address of well if located within city?
1 south, 2 west of Topeka

WATER WELL OWNER: James Jones
 FR#, St. Address, Box #: 5628 SE California Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Topeka, KS 66609 Application Number:

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N					
	---	NW	---	NE	---
		X			
	---	SW	---	SE	---
W					E
					S

DEPTH OF COMPLETED WELL: 100' ft. ELEVATION: ft.
 Depth(s) Groundwater Encountered: 1. 19' ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL: 16' ft. below land surface measured on mo/day/yr 1-12-94
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield: 4 gpm; Well water was ft. after hours pumping gpm
 Bore Hole Diameter: 10" in. to ft., and in. to ft.
 WELL WATER TO BE USED AS:
 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes.....No...X.....; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No

TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded.....

Blank casing diameter: 5" in. to 0-16 ft., Dia 5" in. to 26-98 ft., Dia in. to ft.
 Casing height above land surface: 24" in., weight 2.82 lbs./ft. Wall thickness or gauge No. 258

TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)
 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 16 ft. to 26 ft., From ft. to ft.
 From 98 ft. to 100 ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 14 ft. to 100 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.

GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 0 ft. to 14 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage

Direction from well? SE How many feet? X 300'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	Top Soil			NOTE: 1-21-94 Permission to shallow grout from Rich Harper
1	16	Clay-Brown			
16	20	Pea Gravel-cemented w/ Cherty Limestone			
20	25	Shale-Yellow			
25	50	Shale-Grey			
50	51	Limestone-Grey			
51	59	Shale-Grey			
59	61	Limestone-Grey			
61	65	Shale-Grey			
65	71	Limestone-Grey			
71	72	Shale-Grey			
72	<u>X 79</u>	Limestone-Grey			
79	100	Shale-Grey			

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-12-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 182 This Water Well Record was completed on (mo/day/yr) 2-14-94 under the business name of STRADER DRILLING CO., INC. by (signature) Dale Skren