

CORRECTION(S) TO WATER WELL RECORD (WWC-5)
(to rectify lacking or incorrect information)

Location listed as:

Section-Township-Range: _____

Fraction ($\frac{1}{4}$ $\frac{1}{4}$ $\frac{1}{4}$): _____

County: Douglas
Location changed to:

29 - 12 S - 20 E

NW NE SE

Other changes: Initial statements: Jefferson County

Changed to: Douglas County

Comments: _____

verification method: written & legal descriptions, city street map,
and mapping tool & aerial photos on KGS website.

initials: DRL date: 12/21/2005

submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726
to: Kansas Dept of Health & Environment, Bureau of Water, 1000 SW Jackson, Suite 420, Topeka, KS 66612-1367.

1 LOCATION OF WATER WELL: County: Jefferson Fraction NW 1/4 NE 1/4 SE 1/4 Section Number 29 Township Number T 12 Range Number R 20

Distance and direction from nearest town or city street address of well if located within city? Corner of 9th and Oak St., Lawrence, KS

2 WATER WELL OWNER: FMC Corp. RR#, St. Address, Box #: 1735 Market St. City, State, ZIP Code: Philadelphia, PA 19103 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN 'X' IN SECTION BOX: [Diagram] 4 DEPTH OF COMPLETED WELL 38.4 ft. ELEVATION: 11-09-05. WELL'S STATIC WATER LEVEL 18.2 ft. below land surface measured on mo/day/yr 11-09-05. Pump test data: Well water was ... ft. after ... hours pumping ... gpm. Est. Yield ... gpm: Well water was ... ft. after ... hours pumping ... gpm.

5 TYPE OF BLANK CASING USED: 1 Steel, 2 PVC, 3 RMP (SR), 4 ABS, 5 Wrought iron, 6 Asbestos-Cement, 7 Fiberglass, 8 Concrete tile, 9 Other (specify below). CASING JOINTS: Glued, Clamped, Welded, Threaded. Blank casing diameter 2" in. to 28.4 ft. Dia. Casing height above land surface 0 in. weight ... lbs./ft. Wall thickness or gauge No. SCH 40. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel, 2 Brass, 3 Stainless Steel, 4 Galvanized Steel, 5 Fiberglass, 6 Concrete tile, 7 PVC, 8 RMP (SR), 9 ABS, 10 Asbestos-Cement, 11 Other (Specify), 12 None used (open hole). SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot, 2 Louvered shutter, 3 Mill slot .010, 4 Key punched, 5 Guazed wrapped, 6 Wire wrapped, 7 Torch cut, 8 Saw cut, 9 Drilled holes, 11 None (open hole). SCREEN-PERFORATED INTERVALS: From 28.4 ft. to 38.4 ft. GRAVEL PACK INTERVALS: 10/20 From 27.0 ft. to 21.0 ft.

6 GROUT MATERIAL: 1 Neat cement, 2 Cement grout, 3 Bentonite, 4 Other. Grout Intervals: From 21.0 ft. to 1.0 ft. What is the nearest source of possible contamination: 1 Septic tank, 2 Sewer lines, 3 Watertight sewer lines, 4 Lateral lines, 5 Cess pool, 6 Seepage pit, 7 Pit privy, 8 Sewage lagoon, 9 Feedyard, 10 Livestock pens, 11 Fuel storage, 12 Fertilizer storage, 13 Insecticide storage, 14 Abandoned water well, 15 Oil well/Gas well, 16 Other (specify below) Farm field. Direction from well? How many feet?

Table with columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, PLUGGING INTERVALS. Rows: 0-5 Top soil, 5-10 Sand, 10-20 Fine sand, 20-30 Fine wet sand, 30-40 Fine wet sand. Plugging: 40-27 10/20 silica sand, 27-21 Natural sand, 21-1 3/8 Bentonite chips, 1-0 Cement.

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-09-05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 665 This Water Well Record was completed on (mo/day/yr) 11-10-05 under the business name of Pratt Well Environmental by (signature) Steven Gill