WATER WELL RECORD	Form WWC 5	D: 11	C.W 4	D. D		
1 LOCATION OF WATER WELL:	Form WWC-5				Range Number	
County: [Muglas	1/4 S/4 S/	B4 3		T/2 S	R 20 EW	
Distance and direction from negrect town or city street address of wall if . Clabal Positioning Systems (decimal degrees my of 4 dist)						
logated within kip? What fammed and 500 for Latitude: Longitude: Longitude:						
RR#, St. Address, Box # : 946 E650 Pd		Detumi	Elevation: Datum:			
City, State, ZIP Code : fow much for Collection Method: Data Collection Method:						
3 LOCATE WELL'S 4 DEPTH OF COMPLETED WELL						
LOCATION						
WITH AN "X" IN Depth(s) Gro	Depth(s) Groundwater Encountered (1)					
SECTION BOX: WELL'S STA	WELL'S STATIC WATER LEVEL. 2.7.6.4ft. below land surface measured on mo/day/yr. 1.2.4.0.0 Pump test data: Well water was					
Est. Yield.	Est. Yieldgpm: Well water wasft. afterhours pumpinggpm					
WELL WAT	WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well					
W E I Domestic						
2 Irrigation	2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well					
Was a chemic	- A Was a chemical/bacteriological sample submitted to Department'/ Ves No /\ !If yes mo/day/yrs					
Sample was s	Sample was submitted					
S				*		
5 TYPE OF CASING USED: 5	Wrought Iron 8 Concret	e tile	CASING	G JOINTS: Glued		
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded						
C2 PVC 4 ABS 7 Fiberglass						
Casing height-above-land surface. If F.T. in Weight. lbs/ft. Wall thickness or guage No. Seh 40						
Casing height above land surface						
1 Steel 3 Stainless Steel 5 Fiberglass (7)PVC 9 ABS 11 Other (Specify)						
2 Brass 4 Galvanized Steal 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:						
1 Continuous slot (3)Mill slot 5 Guazed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)						
2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)						
SCREEN-PERFORATED INTERVALS: From						
From						
GRAVEL PACK INTERVALS: From						
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 5 6 ft. to ft. From ft. to ft. From ft. to ft.						
Grout Intervals: From						
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify						
2 Sewer lines 5 Cess		Fuel storage		bandoned water well		
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer Storage 15 Oil well/gas well Direction from well? How many feet?					MAS.KWER	
		FROM TO		PLUGGING INT	FRVAIS	
TROW TO DITE	DEGIC EGG	r ROW 10		1 Edding har	LICYTES	
		56-4	BEN	Honele Holo a	lug	
				2 1		
				- Cal	,	
		4-0	10	psou		

T CONTROL CTORIS OF LAWYOUT PICTURE CENTERING TO THE CONTROL OF THE CONTRO						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)						
Kansas Water Well Contractor's Literase No						
under the business name of floor floor floor business name of floor floor floor (signature)						
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks underline or effect the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone						
785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at						
http://www.kdhe.state.ks.us/geo/waterwells.						