WATER WELL RECORD	Form W	WC-5	D	ivision of Wate	r Resources App. N	lo.	
1 LOCATION OF WATER WELL: County: Douglas	Fraction NE ¼ SW ¼	<i>y</i> ₄ <i>y</i> ₇	Secti		Township No.	Range Number R 20 ZE W	
Street/Rural Address of Well Location	Street/Rural Address of Well Location; if unknown, distance & direction				System (GPS) is	nformation:	
from nearest town or intersection: If at owner's address, check here .			Latit	ude:38.976	2	(in decimal degrees)	
Southeast Corner of N 2nd Street and Elm Street Lawrence, KS			Elev	Longitude: 95.2349 (in decimal degrees) Elevation: 800			
				<u>Datum</u> :			
Bowelbook mills and I owel oo.				Collection Method:			
City State 7TD Code				☐ GPS unit (Make/Model:) ☑ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey			
Lawrence, KS 66044				Est. Accuracy: $\square \triangleleft$ m, \square 3-5 m, \square 5-15 m, $\square >$ 15 m			
3 LOCATE WELL					3 [- 10 111 (L.) · 10 111	
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 46							
SECTION BOX: Depth(s) Grou	[
	WELL'S STATIC WATER LEVELft. below land surface measured on mo/day/yr						
Pun	Pump test data: Well water was						
EST. YIELDgpm. Well water wasft, after hours pumping							
W Bore Hole Diameter 42 in. to .13 ft., and .30 in. to .46 ft.							
WELL WATER TO BE USED AS: □ Public water supply □ Geothermal □ Injection well							
SW SE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)							
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well							
Was a chemical/bacteriological sample submitted to Department? Yes V No							
S If yes, mo/day/yr sample was submitted							
5 TYPE OF CASING USED: Sto	el 🗹 PVC 🔲 C						
CASING JOINTS: Glued CC	amped 🗌 Welded	Threade	d				
Casing diameter .12 in. to .26							
Casing height above land surface12.	in., Weight	.10.35	lbs./1	ft., Wall thic	kness or gange No	o406	
TYPE OF SCREEN OR PERFORATION MATERIAL:							
Steel Stainless Steel PVC Other (Specify)							
Brass Galvanized Steel None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE: Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)							
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)							
SCREEN-PERFORATED INTERVALS: From							
From							
GRAVEL PACK INTERVALS: From. 3 ft. to .46 ft., From							
From ft. to ft., From ft. to ft.							
6 GROUT MATERIAL: Neat cement Cement grout Dentonite Other							
Grout Intervals: From .1	to3 ft., From	************	ft. to	ft.,	From	. ft. toft.	
What is the nearest source of possible cor	ntamination:						
Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)							
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well							

Direction from well					(G (cont) or DI II	CONIC DITTORIAL C	
FROM TO LITHOLO	OIC TOO	FROM	<u>70</u>			GGING INTERVALS	
		3	3 10 E	Native Soil			
			18.5	Bentonite C			
		18.5	46	Clean Pea	Gravel		
				 			
				Typinal 6	E wollo one'te		
				ADICSU TOL	5 wells onsite		
		-		ļ			

		v	. 11	L	—		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☐ constructed, ☐ reconstructed, or ☑ plugged							
under my jurisdiction and was completed on (mo/day/year) .94/18/2012 and this record is true to the best of my knowledge and belief.							
Kansas Water Well Contractor's License No. 509 This Water Well Record was completed on (more and set of Criffin Dewatering, North Central 11 C. hy (cimetary)							
under the business name ofGriffin Dewatering, North Central, LLC							
(white, blue, pink) to Kansas Depar tment of Health and E nvironment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.							
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5,00 for each constructed well. Vi sit us at							
http://www.kdheks.gov/waterweil/index.html.							
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy							