

1 LOCATION OF WELL: County: LEAVENWORTH		Fraction: NE 1/4 NW 1/4 SW 1/4	Section Number: 9	Township Number: T 12 S	Range Number: R 21 E/W
Distance and direction from nearest town or city street address of well if located within city? 1 1/2 east, 2 south of Reno					
2 WATER WELL OWNER: Gene Mosser		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box #: 112 E. 10th Drawer Q		Application Number:			
City, State, ZIP Code: Eudora, KS 66025					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 58' ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 32' ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 21' ft. below land surface measured on mo/day/yr 8-30-91 Pump test data: Well water was ft. after hours pumping gpm Est. Yield 8 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 12" in. to ft. and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued X Clamped			
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile		Welded			
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below)		Threaded			
7 Fiberglass					
Blank casing diameter 5" in. to 0-24 ft. Dia 5" in. to 34-58 ft. Dia					
Casing height above land surface 24" in. weight 2.82 lbs./ft. Wall thickness or gauge No. 258					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)		12 None used (open hole)			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes		10 Other (specify)			
2 Louvered shutter 4 Key punched 7 Torch cut					
SCREEN-PERFORATED INTERVALS: From 24 ft. to 34 ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 23 ft. to 58 ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other hole plug					
Grout Intervals: From 3 ft. to 23 ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		16 Other (specify below)			
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 13 Insecticide storage pond					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard					
Direction from well? east		How many feet? 310'			
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS					
0 5 Top Soil					
5 24 Clay-Brown					
24 26 FS-CS-Med-Pea Chert					
26 28 Clay-Blue					
28 33 FS-CS-Med-Chert 1/2x1-Dirty					
33 47 Limestone-Grey					
47 60 Shale-Grey					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-30-91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 182 This Water Well Record was completed on (mo/day/yr) 9-5-91 under the business name of STRADER DRILLING CO., INC. by (signature) [Signature]					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					