

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Leavenworth		se 1/4 ne 1/4 SW 1/4	9	T 12s S	R 21e E/W
Distance and direction from nearest town or city street address of well if located within city? 1 mile south & 2.5 miles east (linwood)					
2 WATER WELL OWNER: LLOYD or Martha Crowe					
RR#, St. Address, Box # : 1103 Oak ST			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : Eudora, KS 66025			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 45 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 28 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 19 ft. below land surface measured on mo/day/yr 11-20-91			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield 20 gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 12 in. to 20 ft., and 8 in. to 45 ft.			
WELL WATER TO BE USED AS: 1 5 Public water supply 8 Air conditioning 11 Injection well					
① Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)					
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes.....No X; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes X No					
5 TYPE OF BLANK CASING USED: #2					
1 Steel		3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
2 PVC		4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
			7 Fiberglass		Threaded
Blank casing diameter 5 in. to ft., Dia. in. to ft., Dia. in. to ft.					
Casing height above land surface 18 in., weight 284 lbs./ft. Wall thickness or gauge No. 160 psi					
TYPE OF SCREEN OR PERFORATION MATERIAL: #7					
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify)
SCREEN OR PERFORATION OPENINGS ARE: #8					
1 Continuous slot		3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes	
SCREEN-PERFORATED INTERVALS: From 28 ft. to 45 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 24 ft. to 45 ft., From ft. to ft.					
6 GROUT MATERIAL: #3					
1 Neat cement		2 Cement grout	3 Bentonite	4 Other	
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft.					
What is the nearest source of possible contamination: #16					
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
				13 Insecticide storage	Nine mile creek
Direction from well? East		How many feet? 150			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	5	Top Soil			
5	25	Silt			
25	30	FS-CS-Brown			
30	45	Lime			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) #1 11-20-91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 174 This Water Well Record was completed on (mo/day/yr) 11-20-91 under the business name of Breuer Inc by (signature) <i>John S. Breuer</i>					