


1 LOCATION OF WATER WELL: County: <u>LEAVENWORTH</u>	Fraction <u>SE 1/4 SE 1/4 SE 1/4</u>	Section Number <u>13</u>	Township Number <u>T 12 S</u>	Range Number <u>R 21 EW</u>
---	---	-----------------------------	----------------------------------	--------------------------------

Distance and direction from nearest town or city street address of well if located within city?

1/4 mile East of Linwood KS

2 WATER WELL OWNER: <u>Warren H. Gaff Meffler</u> RR#, St. Address, Box #: <u>2004B Linwood Rd</u> City, State, ZIP Code: <u>Linwood, KS 66052</u>	Board of Agriculture, Division of Water Resources Application Number:
--	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: <u>50</u> ft. ELEVATION: Depth(s) Groundwater Encountered 1. <u>26</u> ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL <u>7</u> ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield <u>20</u> gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter <u>8 1/4</u> in. to ft. and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>X</u> No
---	---

5 TYPE OF BLANK CASING USED: <u>#2</u> 1 Steel 3 RMP (SR) <u>2 PVC</u> 4 ABS Blank casing diameter <u>5</u> in. to <u>45</u> ft. Dia <u>X</u> in. to ft. Dia in. to ft. Casing height above land surface <u>24</u> in. weight <u>285</u> lbs./ft. Wall thickness or gauge No. <u>265</u> TYPE OF SCREEN OR PERFORATION MATERIAL: <u>#7</u> 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: <u>#3</u> 1 Continuous slot <u>3 Mill slot</u> 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From <u>45</u> ft. to <u>50</u> ft. From ft. to ft. GRAVEL PACK INTERVALS: From <u>50</u> ft. to <u>26</u> ft. From ft. to ft.	CASING JOINTS: <u>Glued</u> Clamped Welded Threaded
--	---

6 GROUT MATERIAL: <u>#3</u> 1 Neat cement 2 Cement grout <u>3 Bentonite</u> 4 Other Grout Intervals: From <u>26'</u> ft. to <u>4</u> ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination: <u>1 Septic tank</u> 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? <u>NE</u> How many feet? <u>150</u>

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	20	Top soil			
20	26	CLAY BROWN			
26	30	SAND Fine			
30	32	Gravel Fine, Med			
32	50	Gravel Med, Lime			
50		LIME			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1) constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>#1 1-26-93</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>174</u> This Water Well Record was completed on (mo/day/yr) <u>1-29-93</u> under the business name of <u>Breuer Inc</u> by (signature) <u>John S. Breuer</u>
