


1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: LEAVENWORTH	SE 1/4 SE 1/4 NE 1/4	16	T 12 S	R 21 E/W

Distance and direction from nearest town or city street address of well if located within city?

2 W 3/4 N of Linwood

2 WATER WELL OWNER: Debra Lane	(Gene Owen)
RR#, St. Address, Box # : Rt. 1	Board of Agriculture, Division of Water Resources
City, State, ZIP Code : Linwood, KS 66052	Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 120 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 50 ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 46 ft. below land surface measured on mo/day/yr 9-22-87
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield 1 1/2 gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter 8 in. to ft., and in. to ft.
	WELL WATER TO BE USED AS:
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
	Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter 5 in. to 0-40 ft., Dia 5 in. to 60-117 ft., Dia			Threaded
Casing height above land surface 24 in., weight 2.82 lbs./ft. Wall thickness or gauge No. 258			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
11 Other (specify)			12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From 40 ft. to 60 ft.	From ft. to ft.	
	From 117 ft. to 120 ft.	From ft. to ft.	
GRAVEL PACK INTERVALS:	From 20 ft. to 120 ft.	From ft. to ft.	
	From ft. to ft.	From ft. to ft.	

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals:	From 4 ft. to 20 ft.	From ft. to ft.	From ft. to ft.	From ft. to ft.
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
13 Insecticide storage				
Direction from well? W			How many feet? 430	

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Top Soil			
2	12	Clay-Brown			
12	13	Limestone-Grey			
13	21	Shale-Yellow			
21	38	Limestone-Grey			
38	42	Shale-Black			
42	50	Limestone-Grey			
50	54	Shale-Grey			
54	58	Limestone-Grey			
58	65	Shale-Grey			
65	82	Limestone-Grey			
82	112	Shale-Grey			
112	120	Limestone-Grey			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-22-87 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 182 This Water Well Record was completed on (mo/day/yr) 10-19-87 under the business name of Strader Drilling Co., Inc. by (signature) Dale Strader
--

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.