

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: LEAVENWORTH		NE 1/4 NE 1/4 NE 1/4		16		T 12 S		R 21 EW	
Distance and direction from nearest town or city street address of well if located within city?									
2 miles west, 3/4 north of Linwood, KS									
2 WATER WELL OWNER: Curtis McCoy									
RR#, St. Address, Box # : 600 1/2 N. Douglas									
City, State, ZIP Code : Lee's Summit, MO 64063									
Board of Agriculture, Division of Water Resources									
Application Number:									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 60 ft. ELEVATION:							
		Depth(s) Groundwater Encountered 1. 44' ft. 2. ft. 3. ft.							
		WELL'S STATIC WATER LEVEL 19' ft. below land surface measured on mo/day/yr 10-06-89							
		Pump test data: Well water was ft. after hours pumping gpm							
		Est. Yield 15 gpm: Well water was ft. after hours pumping gpm							
		Bore Hole Diameter 12" in. to ft., and in. to ft.							
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well							
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)							
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well							
		Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted							
		Water Well Disinfected? Yes X No							
5 TYPE OF BLANK CASING USED:									
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped									
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded									
7 Fiberglass Threaded									
Blank casing diameter 5" in. to 0-41 ft., Dia in. to ft., Dia in. to ft.									
Casing height above land surface 24" in., weight 2.82 lbs./ft. Wall thickness or gauge No. 258									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement									
2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)									
12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)									
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes									
7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From 41 ft. to 60 ft., From ft. to ft.									
From ft. to ft., From ft. to ft.									
GRAVEL PACK INTERVALS: From 24 ft. to 60 ft., From ft. to ft.									
From ft. to ft., From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other hole plug									
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.									
What is the nearest source of possible contamination:									
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well									
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)									
13 Insecticide storage									
Direction from well? South How many feet? 350'									
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS									
0 27 Clay-Brown									
27 40 Clay-Blue									
40 44 Chert Gravel 1/2x1/2-blue									
44 60 Limestone-Grey									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-06-89 and this record is true to the best of my knowledge and belief. Kansas									
Water Well Contractor's License No. 182 This Water Well Record was completed on (mo/day/yr) 11-15-89									
under the business name of STRADER DRILLING CO., INC. by (signature) Dale Askren									