White—Driller's Copy
Blue—Kansas Geological Survey
Pink—Customer Copy

VBRT

WATER WELL RECORD

DRILLERS LOG OF WELL

FROM (FT.)	TO (FT.)	KIND OF MATERIAL, COLOR, ETC. (NOTE WATER ZONES, AMOUNT, QUALITY)
0	3	Clay
3	24	Sandy Clay
24	30	Sand
30	38	Sand and Gravel

Well Owner: Floyd Mc Comb

Address: Linwood, Kansas

Drilling Contractor: Breuer Drilling Co.

Date Drilled: July 26, 1956

Method of Drilling: Cable Tool

Casing: Used Steel 13# (New, Used—Steel, Galv.—Gage or Weight)

Casing Schedule: 6¼ 38 Feet (Amount, Size, Setting)

Screen Data (if any):

ON COMPLETED WELL

Measured depth to water (Static Level) is 30 ft.

below Land Surface (Land Surface, Top of Casing, Etc.)

TESTED YIELD: 15 gallons per Min. (Min., Hour)

as determined by Bailing (Bailing, Test Pumping, Etc.)

DRAWDOWN: ft. after hrs.

pumping at gal. per minute.

REMARKS:

LOCATION OF WELL

[Show location in Section Plat]

Elev. Tonganoxie ~~80 ft~~ 80

SE NW ¼ SE ¼ Sec. 14

T. 12 S., R. 21 E. W.

County Ber

BR < ~~887~~ 871 D

D = ~~875~~ 877

"To preserve water well information and to promote the conservation, protection, and development of ground-water resources."

26-1633-S—27-32 11-55-3M SETS