


1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Johnson	SE 1/4 NE 1/4 NE 1/4	27	T 12 S	R 22 EW

Distance and direction from nearest town or city street address of well if located within city?

South bank of Kansas River, 2250 ft. east of DeSoto + 395 ft. north of RR

2 WATER WELL OWNER: City of Olathe	RR#, St. Address, Box #: Municipal Service Dept.	Board of Agriculture, Division of Water Resources
City, State, ZIP Code: Highway 7, P.O. Box 768; Olathe, KS 66051-0768	Application Number:	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 70 ft. ELEVATION: approx. 784 ft. msl grade
	Depth(s) Groundwater Encountered 1. 27.06 ft. 2. 28.83 ft. 3. 30.33 ft.
	WELL'S STATIC WATER LEVEL 25.06 ft. below land surface measured on mo/day/yr 9/25/96
	* Pump test data: Well water was 27.06 ft. after 0.5 hours pumping 80 gpm
	Est. Yield gpm: Well water was 28.83 ft. after 0.5 hours pumping 134 gpm
	Bore Hole Diameter 6 in. to 32.27/73 ft. and 0.5 in. to 204 ft.
	WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well observation well
	Was a chemical/bacteriological sample submitted to Department? Yes X No: If yes, mo/day/yr sample was submitted 9/25/96
	Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	10 Asbestos-cement
Blank casing diameter 2 in. to 60 ft. Dia			11 Other (specify)
Casing height above land surface approx. 30 in., weight			12 None used (open hole)
TYPE OF SCREEN OR PERFORATION MATERIAL: *			
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	2 Mill slot	3 Gauzed wrapped	4 Saw cut
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes
SCREEN-PERFORATED INTERVALS:			
From 60 ft. to 70 ft.			
GRAVEL PACK INTERVALS:			
From 60 ft. to 70 ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other 3.5 bags bentonite powder and 1 bucket bentonite pellets
Grout Intervals: From 0 ft. to 30 ft.				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well?				
How many feet?				

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3.5	SILT, CLAYEY, GRAYISH BROWN			
3.5	13	SILT, GRAYISH BROWN, SANDY			
13	30	SILT, GRAYISH BROWN, CLAYEY			
30	33	SILT, SANDY, GRAYISH BROWN			
33	38	SAND, FINE-COARSE GRAY BROWN			
38	41	SAND, F-C SOME FINE GRAVEL			
		GRAY BROWN			
41	51	SAND FINE-COARSE AND GRAVEL FINE			
		COURSE GRAYISH BROWN			
51	57	SAND F-C, SOME GRAVEL F-C GRAYISH BR.			
57	72	SAND M-C AND GRAVEL F-C LIGHT BROWN			
		TRACE-SOME F SAND			
		COARSENING TO MORE GRAVEL WITH DEPTH			
72	72.75	SHALE, WEATHERED DARK GREEN GRAY			
72.75	73	LIMESTONE, HARD			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9/23/96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 578 This Water Well Record was completed on (mo/day/yr) 11/27/96 under the business name of Hydro Group, Inc. by (signature) Michael J. Shea
--