USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

| To 1 41 46 48 53 | Township number |
|------------------------------|--|
| To 1 41 46 48 53 | 52 S. 74th Place ansas City. Kansas 56111 6. Bore hole dia. 6 in. Completion date 10-20- Well depth 70 ft. 7. X Coble tool Rotary Driven Dug Hollow rod Jetted Bored Reverse rotary 8. Use: X Domestic Public supply Industry Irrigation Air conditioning Stock Lown Oil field water Other 9. Casing: Material Ple Height: Above or below Threoded Welded Surface 10 in. RMP PVC X Weight Ibs./ft. Dia 10. Stock In. to ft. depth Wall Thickness: inches or Dia. in. to ft. depth gage No. 219 10. Screen: Manufacturer's name NONE Type Dia. Set between ft. and ft. Gravel pack?NONE ize range of material |
| 1 41 1 46 6 48 8 53 | Well depth 70 ft. 7. X Coble tool _ Rotary _ Driven _ Dug _ Hollow rod _ Jetted _ Bored _ Reverse rotary 8. Use: X Domestic _ Public supply _ Industry _ Irrigation _ Air conditioning _ Stock _ Lown _ Oil field water _ Other 9. Casing: Material _ PLe Height: Above or below _ Threoded _ Welded X Surface _ 18 in. RMP _ PVC X _ Weight _ Ibs./ft. Dia 12 in. to _ ft. depth Wall Thickness: inches or Dia in. to _ ft. depth gage No 219 10. Screen: Manufacturer's name _ NONE Type _ Dia Slot/gauze _ Length _ Set between _ ft. and _ ft ft. Gravel pack?NONE ize range of material _ ft. |
| 1 41 1 46 6 48 8 53 | 10. Screen: Manufacturer's name |
| 1 41 1 46 6 48 8 53 | Set betweenft. andft. Gravel pack? NONE ze range of material |
| 6 48 8 53 | ft. andft. Gravel pack?NONE ze range of material |
| 6 48 8 53 | |
| 1 -1 | |
| | 12. Pumping level below land surfaces: ft. after hrs. pumping g.p.m. |
| 3 55 | ft. afterhrs. pumpingg.p.m. Estimated maximum yield 10 after shot |
| 5 70 | 13. Water sample submitted: mo./day/yr. Yes X No Date 14. Well head completion: X Pitless adopter 18 Inches above grade 15. Well grouted? Yes With: X Neat cement Bentonite Concrete Depth: From 3 ft. to 15 ft. |
| | 16. Nearest source of possible contamination: ft. 200 Direction West Type sept1c Well disinfected upon completion? XX Yes No |
| | 17. Pump: Manufacturer's name Model number Discussion Not installed Jacussion Jacussion HP 1/2 Volts 22 Length of drop pipe 60 ft. capacity 10 g.p.m. Type: |
| | X Submersible Turbine Jet Reciprocating Centrifugal Other |
| torag | 20. Water well contractor's certification: This well was drilled under my jurisdiction and this report Strue to the best of my knowledge and belief. BREUER, INC. Business name License No. Address Signed Address License No. Signed |
| | tora |