VEST

WATER WELL RECORD

DRILLERS LOG OF WELL

	DRILLERS LOG OF WELL
T.D (FT.)	KIND OF MATERIAL, COLOR, ETC. (NOTE WATER ZONES, AMOUNT, QUALITY)
·3 ′	Top-Soil
25	Sandy Clay
27	Sand & gravel
35	Shale-blue
53	Sandstone
69	Shale
83	Lime
90	Slate & Shale
96	Lime
96	T.D.
	<u> </u>
	\(\frac{1}{2}\)
	÷ .
	i
	.3 · 25 27 35 53 69 83 90 96

"To preserve water well information and to promote the conservation, protection, and development of ground-water resources."

Well Owner DR. Larson
Address Farm
Drilling Contractor Breuer Drilling Co.
Basehor, Kansas
Date Drilled 2/17/-67
Method of Drilling Cable Tool (Cable tool, rotary, reverse rotary, etc.)
Casing Schedule 40 ft. New 64 Steel (Amount, Size, Setting—New, Used—Steel, Galv.—Gage or Weight)
(Amount, Size, Setting—New, Used—Steel, Galv.—Gage or Weight)
Screen Data (if any):(Length, Diameter, Slot Size, Setting)
Measured depth to water on completed well (Static Level) i 12 ft. below land surface (Land Surface, Top of Casing, Etc.)
Tested Yield: 4 gallons per min (Min., Hour) as determined by Bailing
as determined by Bailing (Bailing, Test Pumping, Etc.)
TESTED YIELD:
as determined by Bailing (Bailing, Test Pumping, Etc.) DRAWDOWN: ft. after hrs pumping at gal. per minute. REMARKS: This well was shot ffrom 45 to 53 ft. level, with 100 # 75% glyceron. Before shot 2 GPM.
as determined by Bailing (Bailing, Test Pumping, Etc.) Drawdown:ft. afterhrs pumping atgal. per minute. Remarks: This well was shot ffrom 45 to 53 ft. level, with 100 # 75%
as determined by Bailing (Bailing, Test Pumping, Etc.) DRAWDOWN: ft. after hrs pumping at gal. per minute. REMARKS: This well was shot ffrom 45 to 53 ft. level, with 100 # 75% glyceron. Before shot 2 GPM.
as determined by Bailing (Bailing, Test Pumping, Etc.) DRAWDOWN: ft. after hrs pumping at gal. per minute. REMARKS: This well was shot ffrom 45 to 53 ft. level, with 100 # 75% glyceron. Before shot 2 GPM.
as determined by Bailing (Bailing, Test Pumping, Etc.) DRAWDOWN: ft. after hrs pumping at gal. per minute. REMARKS: This well was shot ffrom 45 to 53 ft. level, with 100 # 75% glyceron. Before shot 2 GPM.
as determined by Bailing (Bailing, Test Pumping, Etc.) DRAWDOWN:ft. afterhrs pumping atgal. per minute. REMARKS: This well was shot ffrom 45 to 53 ft. level, with 100 # 75% glyceron. Before shot 2 GPM. after shot 4 GPM. Storage 1800 gal.
as determined by Bailing (Bailing, Test Pumping, Etc.) DRAWDOWN:
as determined by Bailing (Bailing, Test Pumping, Etc.) DRAWDOWN:
as determined by Bailing (Bailing, Test Pumping, Etc.) DRAWDOWN:
as determined by Bailing (Bailing, Test Pumping, Etc.) DRAWDOWN:
as determined by Bailing (Bailing, Test Pumping, Etc.) Drawdown:ft. afterhrs pumping atgal. per minute. Remarks: This well was shot ffrom 45 to 53 ft. level, with 100 # 75% glyceron. Before shot 2 GPM. after shot 4 GPM. Storage 1800 gal. Location of Well Topographic Sheet Show location in Section Plat] Start Show location in Section Plate Storage 1800 gal.

27-1467-S--27-32