

12-22-10 da

located on Top Kan  
 Study map  
 188T

# WATER WELL RECORD

## DRILLERS LOG OF WELL

FROM (FT.)	TO (FT.)	KIND OF MATERIAL, COLOR, ETC. (NOTE WATER ZONES, AMOUNT, QUALITY)
0	5	Top Soil.
5	10	Rock Broken
10	17	Shale Dark
17	25	Lime
25	45	Shale
45	62	Lime
62	63	Shale
63	79	Lime
79	81	Shale
81	91	Lime
91	93	Shale
93	96	Lime
96	99	Shale
99	118	Lime
118	163	Lime-soft- Arg.
163	166	Shale
166	172	Lime
172	176	Slate- dark-water
176	180	Lime
180		SHALE Slate T.D.

Well Owner Zimmerlin  
 Address 4 Miles S. W. Bonner Springs  
 Drilling Contractor Beruer Drilling Co.  
 Date Drilled May 1 1955  
 Method of Drilling Cabel Tool  
 Casing: None  
(New, Used—Steel, Galv.—Gage or Weight)  
 Casing Schedule: None (Amount, Size, Setting)  
Water Heater 5 ft. 12" Di.  
 Screen Data (if any): None

## ON COMPLETED WELL

Measured depth to water (Static Level) is 110 ft.  
 below Land Surface  
(Land Surface, Top of Casing, Etc.)  
 TESTED YIELD: \_\_\_\_\_ gallons per \_\_\_\_\_  
(Min., Hour)  
 as determined by \_\_\_\_\_  
(Bailing, Test Pumping, Etc.)  
 DRAWDOWN: \_\_\_\_\_ ft. after \_\_\_\_\_ hrs.  
 pumping at \_\_\_\_\_ gal. per minute.


## REMARKS:

Appox 70 ft. water Overnight

## LOCATION OF WELL

[Show location in Section Plat]

Elev. 900



NE  $\frac{1}{4}$  SE  $\frac{1}{4}$  Sec. 10

T. 12 S., R. 22 E.

County Leavenworth

"To preserve water well information and to promote the conservation, protection, and development of ground-water resources."



4