

Range Number  
R 22 (E) WRange Number  
R 22 (E) W

**Global Positioning Systems** (decimal degrees, min. of 4 digits)  
Latitude: 38.996912  
Longitude: -95.002222  
Elevation: unknown  
Datum: NAD 27  
Data Collection Method: WAAS GPS Unit

Datum: NAD 27

**Data Collection Method: WAAS GPS Unit**

4 DEPTH OF COMPLETED WELL \_\_\_\_\_ 60 \_\_\_\_\_ ft.

Depth(s) Groundwater Encountered (1) \_\_\_\_\_ ft. (2) \_\_\_\_\_ ft. (3) \_\_\_\_\_ ft.

WELL'S STATIC WATER LEVEL 21.25 ft. below land surface measured on mo/day/yr. 2-1-06

Pump test data: Well water was not checked ft. after \_\_\_\_\_ hours pumping \_\_\_\_\_ gpm

Est. Yield unknown gpm: Well water was \_\_\_\_\_ ft. after \_\_\_\_\_ hours pumping \_\_\_\_\_ gpm

WELL WATER TO BE USED AS:

5	Public water supply	8	Air conditioning	11	Injection well				
1	Domestic	3	Feedlot	6	Oil field water supply	9	Dewatering	12	Other (Specify below)
2	Irrigation	4	Industrial	7	Domestic (lawn & garden)	10	Monitoring well		

Was a chemical/bacteriological sample submitted to Department? Yes \_\_\_\_\_ No ☒ If yes, mo/day/yr \_\_\_\_\_

Sample was submitted \_\_\_\_\_ Water well disinfected? Yes \_\_\_\_\_ No ☒

<b>5 TYPE OF CASING USED:</b>		5 Wrought Iron	8 Concrete tile	CASING JOINTS: Glued _____ Clamped _____	
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded _____	
② PVC	4 ABS	7 Fiberglass		Threaded _____	✓
Blank casing diameter	2	in. to	48	ft., Diameter	
Casing height above land surface	24	in., weight	.70	lbs./ft. Wall thickness or gauge No.	154

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless Steel	5 Fiberglass	7 PVC	9 ABS	11 Other (Specify)
2 Brass	4 Galvanized Steel	6 Concrete tile	8 RM (SR)	10 Asbestos-Cement	12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot	5 Gauzed wrapped	7 Torch cut	9 Drilled holes	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	8 Saw Cut	10 Other (Specify)	

SCREEN-PERFORATED INTERVALS: From 48 ft. to 58 ft., From ft. to ft.

From ft. to ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 20 ft. to 62 ft., From ft. to ft.

From ft. to ft., From ft. to ft.

**6 GROUT MATERIAL:** 1 Neat Cement 2 Cement grout 3 Bentonite 4 Other \_\_\_\_\_ Bentonite Holeplug \_\_\_\_\_

Grout Intervals: From \_\_\_\_\_ ft. to \_\_\_\_\_ ft., From \_\_\_\_\_ ft. to \_\_\_\_\_ ft., From 0 ft. to 20 ft.

What is the nearest source of possible contamination:					
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	13 Insecticide Storage	16 Other (specify below)
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	14 Abandoned water well	None known
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer Storage	15 Oil well/gas well	

Direction from well? \_\_\_\_\_ How many feet? \_\_\_\_\_

[illegible]

7 **CONTRACTOR'S OR LANDOWNER'S CERTIFICATION:** This water well was (1) constructed (2) reconstructed (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-1-06 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 185 This Water Well Record was completed on (mo/day/year) 2-9-06 Under the business name of Clarke Well & Equipment, Inc. by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.