WATER WELL RECORD		Form WWC-5		Division of Water Resources; App. No.				
1 LOCATION OF WATER WELL: County: Johnson		NW 1/4 NW 1/4 N		Section Number 28		Township Number T 12 S		
Distance and direction from nearest town or city street address of well if located within city? Approximately 1/4 mile north of De Soto					Global Positioning Systems (decimal degrees, min. of 4 digits) Latitude: Longitude:			
2 WATER WELD RR#, St. Addre City, State, ZIP	6051		Elevation: unknown Datum: Data Collection Method:					
3 LOCATE WEI LOCATION WITH AN "X" SECTION BOX N NWNE	Depth(s) Groundwat WELL'S STATIC W Pump test d Est. Yield unknown g WELL WATER TO 1 Domestic 3 2 Irrigation 4 Was a chemical/bace	PLETED WELL er Encountered (1) /ATER LEVEL 23.4 ata: Well water was no pm: Well water was per BE USED AS: 5 Pub Feedlot 6 Oil fiel Industrial 7 Domesteriological sample subned	t checke lic water d water stic (lawr	ft. t. below lar ed ft. afterft. after supply supply n & garden) Departme	ft. (2) and surface 8 Air c 9 Dew 10 Mon nt? Yes	ft. (3) the measured on mo/da hours pumping hours pumping tonditioning 11 I atering 12 (itoring well No	ft, y/yr2-3-06 gpm gpm njection well Other (Specify below) If yes, mo/day/yrs	
STYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Threaded Lasing diameter 2 in. to 35 ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface 24 in., weight .70 lbs./ft. Wall thickness or gauge No154 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass .7 PVC 9 ABS 11 Other (Specify) 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (Specify) SCREEN-PERFORATED INTERVALS: From 35 ft. to 45 ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 20 ft. to 46 ft., From ft. to ft. From ft. to ft., From ft. to ft.								
From ft. to ft., From ft. to ft.								
Grout Intervals: From ft. to ft., From ft., Fro								
FROM TO	LITHOLOGIC I	.OG	FROM			PLUGGING INTI	ERVALS	
0 2	Topsoil							
2 7 7 12	Limestone, yellow, soft							
12 34	Clay, dark gray, hard Sand and gravel, mediu	m to fine						
34 35	Limestone, soft, yellow							
35 45	Sand and gravel, fine to	coarse						
45 46	Limestone, yellow							
	31-00-				<u> </u>			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-3-06 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 185 This Water Well Record was completed on (mo/day/year) 2-9-06 Under the business name of Clarke Well & Equipment, Inc. by (signature)								
copies to Kansas Depart	INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each <u>constructed</u> well.							

8078

MW 10-06