

1 LOCATION OF WATER WELL: County: Johnson Fraction NW 1/4 NW 1/4 SE 1/4 Section Number 20 Township Number T 12 S Range Number R 22 E W

Distance and direction from nearest town or city street address of well if located within city? Approximately 3/4 mile north and 1/2 mile west of DeSoto Global Positioning Systems (decimal degrees, min. of 4 digits) Latitude: 38.992239 Longitude: -94.991503 Elevation: unknown Datum: NAD 27 Data Collection Method: WAAS GPS Unit

2 WATER WELL OWNER: City of Olathe RR#, St. Address, Box # : P.O. Box 768 City, State, ZIP Code : Olathe, KS 66051

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 4-section grid with 'X' in the SE section] 4 DEPTH OF COMPLETED WELL 60 ft. Depth(s) Groundwater Encountered (1) ft. (2) ft. (3) ft. WELL'S STATIC WATER LEVEL 28.26 ft. below land surface measured on mo/day/yr 2-14-06 Pump test data: Well water was not checked ft. after hours pumping gpm Est. Yield unknown gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 12 Other (Specify below) Observation Well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No [checked] If yes, mo/day/yrs Sample was submitted Water well disinfected? Yes No [checked]

5 TYPE OF CASING USED: 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) 2 PVC 4 ABS 7 Fiberglass 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped Welded Threaded Blank casing diameter 2 in. to 48 ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface 24 in., weight .70 lbs./ft. Wall thickness or gauge No. 154

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 9 ABS 11 Other (Specify) 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (Specify) SCREEN-PERFORATED INTERVALS: From 48 ft. to 58 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 20 ft. to 60 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat Cement 2 Cement grout 3 Bentonite 4 Other Bentonite Holeplug Grout Intervals: From ft. to ft., From ft. to ft., From 0 ft. to 20 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify below) 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 14 Abandoned water well None known 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer Storage 15 Oil well/gas well

Direction from well? How many feet? LITHOLOGIC LOG PLUGGING INTERVALS

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	6	Topsoil			
6	16	Clay, dark brown			
16	36	Sand and gravel, fine to medium, tan			
36	52.2	Sand and gravel, fine to medium with large rock			
52.2	60	Limestone, gray and white			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-14-06 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 185 This Water Well Record was completed on (mo/day/year) 2-28-06 Under the business name of Clarke Well & Equipment, Inc. by (signature)